

(NASA-CR-165623-Vol-5) THERMAL POLLUTION
MATHEMATICAL MODEL. VOLUME 5: USER'S
MANUAL FOR THREE-DIMENSIONAL RIGID-LID MODEL
Final Report (Miami Univ.) 154 p
HC A08/MF A01

N81-23558

Unclas
CSCL 13B G3/43 23983

**THERMAL POLLUTION MATHEMATICAL
MODEL**

(Volume Five of Seven Volumes)

USER'S MANUAL FOR THREE-DIMENSIONAL RIGID-LID MODEL

Volume V

by

**Samuel S. Lee, Subrata Sengupta,
Emmanuel V. Nwadike and Sumon K. Sinha
Department of Mechanical Engineering
University of Miami
Coral Gables, Florida 33124**



Prepared for

**National Aeronautics and Space Administration
and
Environmental Protection Agency
(NASA Contract NAS 10-9410)**

August 1980

STANDARD TITLE PAGE

1. Report No. CR-165623	2. Government Accession No.	3. Recipient's Catalog No.	
4. Title and Subtitle Thermal Pollution Math Model Volume V, User's Manual for Three-Dimensional Rigid-Lid Model		5. Report Date	
		6. Performing Organization Code TR 43-4	
7. Author(s) Drs. Samuel Lee and Subrata Sengupta; Emmanuel V. Nwadike and Sumon K. Sinha		8. Performing Organization Report No.	
9. Performing Organization Name and Address John F. Kennedy Space Center Kennedy Space Center, Florida 32899 Project Manager: Roy A. Bland Code PT-FAP		10. Work Unit No.	
		11. Contract or Grant No. NAS10-9410	
12. Sponsoring Agency Name and Address National Aeronautics and Space Administration and Environmental Protection Agency Research Triangle Park, N.C.		13. Type of Report and Period Covered Final	
		14. Sponsoring Agency Code	
15. Abstract The three-dimensional rigid-lid model was developed by the thermal pollution group at the University of Miami and verified for accuracy at various sites. The model results have been found to be fairly accurate in all the verification runs. The model is intended to be used as a predictive tool in future sites and this manual has been written to enable any user to be able to apply it without difficulty.			
16. Key Words Thermal Pollution Math Models Nuclear or Fossil Fuel Power Plants Waste Heat			
17. Bibliographic Control Announce in Star Category 43		18. Distribution Unlimited	
19. Security Classif.(of this report) None	20. Security Classif.(of this page) None	21. No. of Pages	22. Price

PREFACE

The three-dimensional rigid-lid model is intended to be used for hydrothermal predictions of closed basins subjected to a heated discharge together with various other inflows and outflows. This volume has been written in order to assist any prospective user in applying the model to specific sites. Derivation of the governing equations and various other details have been omitted. The programs are fairly general and only one subroutine and a data file has to be rewritten for specific cases.

This work was sponsored by the National Aeronautics and Space Administration (NASA-KSC) and the Environmental Protection Agency (EPA-RTP).

ABSTRACT

The three-dimensional rigid-lid model was developed by the thermal pollution group at the University of Miami and verified for accuracy at various sites. The model results have been found to be fairly accurate in all the verification runs. The model is intended to be used as a predictive tool in future sites and this manual has been written to enable any user to be able to apply it without difficulty.

CONTENTS

Preface	ii
Abstract	iii
Figures	v
Tables	vi
Symbols	vii
Acknowledgments	viii
1. Introduction	1
2. Recommendations	2
3. Program Description and Flow Chart	3
Description of program algorithm	3
Flow chart	3
Subroutine descriptions	3
4. List of Program Symbols Used in Main Program	6
Description of main variables	6
Marker matrices	11
5. Preparation of Runs	13
6. Input Data	14
7. Plotting Programs	15
Description of plot programs	15
Subroutines	15
References	16
Appendices	17
A. Example Case	18
Introduction	18
Problem statement	18
Calculations of parameters and input data	20
Sample input	22
Lake Keowee execution deck	24
B. Fortran Source Program Listing	45
List of main program and subroutines	46
List of plot programs	47
Sample run	120
Sample plots	138

FIGURES

<u>Number</u>		<u>Page</u>
1	Flow chart (main program)	30
2	Coordinates and grid system	32
3	Map of Lake Keowee	37
4	Lake Keowee (region of interest)	38
5	MAR matrix	39
6	MRH matrix	40
7	Keowee hydro discharge, February 27, 1979	43
8	Jocassee-pumped storage station discharge, February 27, 1979	44

TABLES

<u>Number</u>		<u>Page</u>
1	Governing Equations	5
2	Subroutines for Calculations	26
3	Input Data to Main Program	33
4	Subroutines for Plots	36
5	Meteorological Data for Lake Keowee, February 27, 1979 ..	41
6	Summary of Inflows and Outflows to Lake Keowee, February 27, 1979	42

SYMBOLS

A_H	Horizontal kinematic eddy viscosity	T	Temperature
A_V	Vertical kinematic eddy viscosity	T_{ref}	Reference temperature
A_{ref}	Reference kinematic eddy viscosity	T_e	Equilibrium temperature
A_V^*	A_V/A_{ref}	T_s	Surface temperature
B_H	Horizontal eddy thermal diffusivity	t	Time
B_V	Vertical eddy thermal diffusivity	t_{ref}	Reference time
B_{ref}	Reference eddy thermal diffusivity	u_{ref}	Velocity in x-direction
B_V^*	B_V/B_{ref}	v	Velocity in y-direction
C_p	Specific heat at constant pressure	w	Velocity in z-direction
Eu	Euler number	x	Horizontal coordinate
f	Coriolis parameter	y	Horizontal coordinate
g	Acceleration due to gravity	z	Vertical coordinate
h	Depth relative to the mean water level		
H	Reference depth		
I	Grid index in x-direction or α -direction		
J	Grid index in y-direction or β -direction		
K	Grid index in z-direction or γ -direction		
K_S	Surface heat transfer coefficient		
L_S	Horizontal length scale		
P	Pressure		
P_S	Surface pressure		
Pr	Turbulent Prandtl number, A_{ref}/B_{ref}		
Pe	Peclet number		
Q	Heat sources or sinks		
Re	Reynolds number (turbulent)		
Ri	Richardson number		

<u>Greek Letters</u>	
α	Horizontal coordinate in stretched system, = x
β	Horizontal coordinate in stretched system, = y
γ	Vertical coordinate in stretched system
σ	Constant in vertical diffusivity equation, or vertical coordinate in stretched system, = Z/H
Ω	Transformed vertical velocity
ρ	Density
τ_{xz}	Surface shear stress in x-direction
τ_{yz}	Surface shear stress in y-direction
$\overline{(\quad)}$	Dimensional quantity
$(\bar{\quad})$	Dimensional mean quantity
(\cdot)	Dimensional quantity
(\quad)	Dimensional quantity
$(\quad)_{ref}$	Reference quantity

ACKNOWLEDGMENTS

This work was supported by a contract from the National Aeronautics and Space Administration (NASA-KSC) and the Environmental Protection Agency (EPA-RTP).

The authors express their sincere gratitude for the technical and managerial support of Mr. Roy A. Bland, the NASA-KSC project manager of this contract, and the NASA-KSC remote sensing group. Special thanks are also due to Dr. Theodore G. Brna, The EPA-RTP project manager, for his guidance and support of the experiments, and to Mr. S. B. Hager, Chief Engineer, Civil-Environmental Division, and Mr. William J. McCabe, Assistant Design Engineer, both from the Duke Power Company, Charlotte, North Carolina, and their data collection group for data acquisition. The support of Mr. Charles H. Kaplan of EPA was extremely helpful in the planning and reviewing of this project.

SECTION 1

INTRODUCTION

The need for mathematical modeling in predicting and monitoring thermal pollution was discussed in previous reports by Veziroglu et al. (1973, 1974). Predictive studies of ecosystems can only be made by mathematical models. A prior knowledge of the effects of disturbances is essential for environmental impact studies. Thus, the mathematical model is a crucial tool in decisions involving power plant siting, land development, etc.

The University of Miami team undertook development of a methodology using remote sensing and numerical modeling to study thermal pollution. The use of remotely-sensed data in modeling has been discussed by Sen-gupta et al. (1974). The remote sensing effort has been discussed in detail in previous publications. This volume has been written so as to enable a user to apply the mathematical model to new sites for predictive purposes.

The hydrodynamics and thermodynamics of an ecosystem are controlled by geometry, meteorological conditions and physical characteristics of the water such as density, salinity and turbidity. In this model the effects of salinity and turbidity have been neglected. Hence, the governing equations are composed of the three-dimensional Navier-Stokes equations and the energy equation. Various assumptions can be made for different situations leading to simplification or elimination of equations. The main simplifying assumption in this case is the rigid-lid assumption. This means that surface height fluctuations are not simulated by this model, and this is a reasonable assumption for most applications (e.g., Lakes).

The rigid-lid model has the following capabilities:

1. It predicts the wind-driven circulation.
2. It predicts the circulation caused by inflows and outflows to the domain.
3. It predicts the thermal effects in the domain.
4. It combines the aforementioned processes.

The calibration procedure consists of comparing ground-truth corrected airborne radiometer data with surface isotherms predicted by the model.

SECTION 2

RECOMMENDATIONS

Various numerical models have been developed to study the effects of heated discharge and meteorological conditions on bodies of water. Most of these models are one or two dimensional. These models have a high computational speed but only give horizontally or vertically averaged values of temperatures.

Three-dimensional models, however, have a much finer resolution but they consume larger computer time. The three-dimensional rigid-lid model can be used to obtain detailed temperature and velocity distributions in a domain where surface gravity waves are small compared to the depth of the domain. This model, as compared to free-surface models, runs faster since surface gravity waves are eliminated by the rigid-lid assumption.

A proper method of using this model would be to run a one-dimensional model initially to obtain a rough picture of the temperatures and then using this model to obtain a better resolution, the 1-D results being used as ambient conditions.

The following improvements have been suggested for the model.

1. Since all natural flows are turbulent, proper turbulent closures are needed to make the model meaningful. At present, the simplest possible closures, namely constant eddy viscosities and eddy diffusivities, have been used. However, better results may be obtained by using a higher order closure.
2. At present, the model uses uniform horizontal grids and stretched vertical grids. Nonuniform horizontal grids could be introduced for better resolution near the boundaries.
3. The program has been written to be run as a batch-job on the computer. It could be made interactive so as to enable the user to run it on a terminal. However, this would require some modifications in order to reduce the storage space.

SECTION 3

PROGRAM DESCRIPTION AND FLOW CHART

DESCRIPTION OF PROGRAM ALGORITHM

The governing equations for a body of water which are derived from the basic laws of conservation of mass, momentum and energy are shown in Table 1. These equations incorporate a vertically-stretched coordinate system so as to make the model general enough to handle any kind of bottom topography. The problem is set up as an initial value problem. The initial values of the water velocities and temperatures are specified and the model is run so as to give the values of the above quantities in subsequent time periods using an explicit scheme. The sequence of the calculations are as follows:

1. The initial values of the velocities and temperatures are read into the program, the region of interest within the basin being classified into interior, corner or boundary points. (Subroutines used are READ 3K, INITIA, INITIT, HEIGHT.)
2. The data, which includes the boundary conditions such as the various meteorological parameters like surface wind speed, air temperature, humidity and solar radiation are read into the program using subroutine READ2.
3. Depending on the site chosen, the various discharges (volume flow rate, velocities and temperatures) in and out of the basin are read into the model. These are incorporated in the subroutine INLET1.
4. The momentum, continuity and energy equations are now solved to determine the velocities and temperatures in the subsequent time steps. The predictive equation for pressure (viz., the Poisson equation) is solved iteratively to determine the pressures at various points of the domain. (Note: Because of the rigid-lid assumption, the surface or lid pressure is no longer atmospheric.)

THE PROGRAM FLOW CHART IS SHOWN IN FIGURE 1

The various subroutines used are as well as a brief description of their functions are shown in Tables 2 and 3.

Symbols Used in Governing Equations

(Quantities with bar are dimensional)

$\tilde{\rho}$ = density

\tilde{T} = temperature

$$\tilde{\omega} = \gamma \left(u \frac{\partial \tilde{h}}{\partial x} + v \frac{\partial \tilde{h}}{\partial x} \right) + \tilde{h} \tilde{\Omega}$$

$$\tilde{\Omega} = \frac{\partial \gamma}{\partial \tilde{t}}$$

$$\gamma = \tilde{z} / \tilde{h}(n) \gamma$$

$$\beta = \tilde{y} / L$$

$$\alpha = \tilde{x} / L$$

$$u = \tilde{u} / U_{\text{ref}}$$

$$v = \tilde{v} / U_{\text{ref}}$$

$$w = \tilde{w} / U_{\text{ref}}$$

$$t = \tilde{t} / t_{\text{ref}}$$

$$\varepsilon = H / L$$

$$P = \tilde{P} / P_{\text{ref}} U_{\text{ref}}^2$$

$$T = \frac{\tilde{T} - T_{\text{ref}}}{T_{\text{ref}}}$$

$$\rho = \frac{\tilde{\rho} - \rho_{\text{ref}}}{\rho_{\text{ref}}}$$

$$A_H^* = A_H / A_{\text{ref}} \quad \text{nondimensional horizontal eddy viscosity}$$

$$A_V^* = A_V / A_{\text{ref}} \quad \text{nondimensional vertical eddy viscosity}$$

$$B_H^* = B_H / B_{\text{ref}} \quad \text{nondimensional horizontal eddy viscosity}$$

$$B_V^* = B_V / B_{\text{ref}} \quad \text{nondimensional vertical eddy viscosity}$$

$$R_e = (U_{\text{ref}} L) / A_{\text{ref}}, \quad R_B = U_{\text{ref}} / f L, \quad P_r = A_{\text{ref}} / B_{\text{ref}}$$

$$P_e = R_e, \quad P_r, \quad E_u = g H / U_{\text{ref}}^2$$

Table 1. Governing Equations

Continuity Equation:

$$\frac{\partial(hu)}{\partial \alpha} + \frac{\partial(hv)}{\partial \beta} + h \frac{\partial \Omega}{\partial \gamma} = 0$$

Momentum Equation:

$$\begin{aligned} & \frac{\partial(hu)}{\partial t} + \frac{\partial(huu)}{\partial \alpha} + \frac{\partial(huv)}{\partial \beta} + h \frac{\partial(\Omega u)}{\partial \gamma} - \frac{h}{R_B} v \\ &= -h \frac{\partial P_s}{\partial \alpha} - h B_x + \frac{1}{R_e} \frac{\partial}{\partial \alpha} (h \frac{\partial}{\partial \alpha}) + \frac{1}{R_e} \frac{\partial}{\partial \beta} (h \frac{\partial v}{\partial \beta}) \\ & \quad + \frac{1}{E^2 R_e} \frac{1}{h} \frac{\partial}{\partial \gamma} (A_v^* \frac{\partial u}{\partial \gamma}) \end{aligned}$$

and

$$\begin{aligned} & \frac{\partial(hv)}{\partial t} + \frac{\partial(huv)}{\partial \alpha} + \frac{\partial(hvv)}{\partial \beta} + h \frac{\partial(\Omega v)}{\partial \gamma} + \frac{h}{R_B} u \\ &= -h \frac{\partial P_s}{\partial \beta} - h B_y + \frac{1}{R_e} \frac{\partial}{\partial \alpha} (h \frac{\partial v}{\partial \alpha}) + \frac{1}{R_e} \frac{\partial}{\partial \beta} (h \frac{\partial v}{\partial \beta}) \\ & \quad + \frac{1}{E^2 R_e} \frac{1}{h} \frac{\partial}{\partial \gamma} (A_v^* \frac{\partial v}{\partial \gamma}) \end{aligned}$$

Hydrostatic Equation:

$$\frac{\partial P}{\partial \gamma} = E_u (1 + \rho) h$$

Energy Equation:

$$\begin{aligned} & \frac{\partial(hT)}{\partial t} + \frac{\partial(huT)}{\partial \alpha} + \frac{\partial(hvT)}{\partial \beta} + h \frac{\partial(\Omega T)}{\partial \gamma} \\ &= \frac{1}{P_e} \frac{\partial}{\partial \alpha} (h \frac{\partial T}{\partial \alpha}) + \frac{1}{P_e} \frac{\partial}{\partial \beta} (h \frac{\partial T}{\partial \beta}) + \frac{1}{P_e E^2} \frac{1}{h} \frac{\partial}{\partial \gamma} (B_v^* \frac{\partial T}{\partial \gamma}) \end{aligned}$$

SECTION 4

LIST OF PROGRAM SYMBOLS USED IN MAIN PROGRAM

DESCRIPTION OF MAIN VARIABLES

A. A - constant in equation of state, $\rho = A + BT + CT^2$

AREF - reference eddy viscosity

AA - value of 'V' at plume inlet

ABR - 1/Rossby number

AH - 1/Reynolds number

AI - coefficient in front of pressure term

AKT - $(K_s)(H_{ref})/(B_z)$

AP - coefficient in front of pressure term

ARBP - arbitrary pressure

AV - $\frac{1}{\epsilon^2 R_E}$ where $\epsilon = \frac{H}{L}$

A3 - normalized vertical eddy coefficient of viscosity

ANGLE - wind direction angle

B. B - constant in equation of state, $\rho = A + BT + CT^2$

BB - value of 'V' at plume inlet (at $l=10$)

BZ - $\rho C_p B_v$

BV - normalized vertical eddy diffusivity, normalized with respect to reference eddy diffusivity

C. C - constant in equation of state, $\rho = A + BT + CT^2$

CC - value of γ (constant)

CW - temperature gradient at vertical boundaries

CB - temperature gradient at the bottom

D. D - U at previous time step

$$D1TZ = \frac{\partial T}{\partial Z}$$

$$DPX = \frac{\partial P}{\partial x}$$

$$DPY = \frac{\partial P}{\partial y}$$

$$DPSX = \frac{\partial P_s}{\partial x}$$

$$DPSY = \frac{\partial P_s}{\partial y}$$

DT - time increment

DX - increment in x-direction

DY - increment in y-direction

DZ - increment in Z-direction

$$D1HUX = \frac{\partial (hu)}{\partial x}$$

$$D1HUY = \frac{\partial (hv)}{\partial y}$$

$$D1HUUX = \frac{\partial (huu)}{\partial x}$$

$$D1HUVY = \frac{\partial (huv)}{\partial y}$$

$$D1HVVY = \frac{\partial (hvv)}{\partial y}$$

$$D1UY = \frac{\partial u}{\partial y}$$

$$D1VX = \frac{\partial v}{\partial x}$$

$$D2UX = \frac{\partial^2 u}{\partial x^2}$$

$$D2VX = \frac{\partial^2 v}{\partial x^2}$$

$$D1VWX = \frac{\partial (vw)}{\partial Z}$$

$$D1UZ = \frac{\partial u}{\partial Z}$$

$$D2UZ - \frac{\partial^2 u}{\partial Z^2}$$

$$D1VZ - \frac{\partial v}{\partial z}$$

$$D2VZ - \frac{\partial^2 v}{\partial Z^2}$$

$$D1A3Z - \frac{\partial A^3}{\partial Z}$$

$$DLZ - \frac{(DX^2)(DY^2)}{(DX)^2(DY)^2}$$

E. E - V at previous time step

EPS - convergence criterion

EUL - Euler number

EX - residual error in pressure iteration

F. FH - forcing function in pressure equation

FW - factor in wind stress calculation formula

G. G - dummy variable for V (for future time step)

H. H - dummy variable for U (for future time step)

HI - nondimensional depth = $\frac{h}{H}$

HREF - reference depth

$$HX - \frac{\partial H}{\partial x}$$

$$HY - \frac{\partial H}{\partial y}$$

I. IN - maximum number of grid points in x-direction

IWN - maximum number of half-grid points in x-direction, IWN = IN - 1

I - index of x-axis, main grid

ITN - Index for number of iterations

IW - index for x-axis, half grid

IRUN - index for number of runs
 = 0, first run
 = 1, from second time onwards

ISGNX, ISGNY - determine signs of TAUX and TAUY respectively

J. J - index for y-axis, main grid

JW - index for y-axis, half grid

JWN - maximum number of half-grid points in y-direction
 $JWN = JN - 1$

JN - maximum number of main grid points in y-direction

K. K - index for Z-axis

KSTORE - specified usage of tape for storing results

KN - maximum number of main grid points in Z-direction

KISS - surface heat transfer coefficient (nondimensional)

L - maximum length of the domain

LN - number of time steps to be computed

LLN - total number of time steps/LN

M. MAR - number to describe general location of a point in the main grid

MRH - number to describe general location of a point in the half grid

MAXIT - maximum number of iterations

O. OMEGA - relaxation factor

P. P - nondimensional pressure

PN - New pressure, nondimensional

PINTH - dummy variable for pressure (future time step)

R. R - dimensional density at main grid points

RE - Reynolds number

RB - Rossby number

RINTX - density integrated with respect to x

RINTY - density integrated with respect to y

RO - nondimensional density at main grid points
 ROW - nondimensional density at half grid points
 RREF - reference density (gm/cc)
 RW - dimensional density at half grid points (gm/cc)
 RADN - solar radiation (w/m²)
 T. T - nondimensional temperature at main grid points
 TO - initial temperature (dimensional) (°C)
 TAMB - ambient temperature (dimensional) (°C)
 TAIR - air temperature (dimensional) (°C)
 TAI - coefficient in front of convective terms in the energy equation, = 1.
 TAH - $\frac{1}{P_e}$ where $P_e = R_e \times P_r$
 TAV - $\frac{1}{P_e \epsilon^2}$ where $\epsilon = \frac{H}{L}$
 TE - equilibrium temperature (dimensional) (°C)
 TTOT - total time elapsed
 TAUX - $\partial u / \partial \gamma$ (nondimensional)
 TAUY - $\partial v / \partial \gamma$ (nondimensional)
 TEM - dimensional temperature at main grid points
 TEMW - dimensional temperature at half-grid points
 TREF - reference temperature
 TW - nondimensional temperature at half-grid points
 TLL - temperature at the discharge point (nondimensional)
 TSU - water surface temperature (nondimensional)
 TDEW - dewpoint temperature (dimensional)
 U. U - velocity in x-direction (nondimensional)
 V. V - velocity in y-direction (nondimensional)

- VVIS - vertical eddy viscosity (nondimensional)
- W. W - velocity in Z-direction (nondimensional)
- WH - W at half-grid points
- WHLDT - time derivative of WH at lid (i.e., $\frac{\partial}{\partial t}(WH)/Z = 0$)
- X. XINT - integral of x terms on the right-hand side of Poisson's equation
- X - horizontal coordinate across discharge
- Y. YINT - integral of y terms on the right-hand side of Poisson's equation
- Y - horizontal coordinate across discharge
- Z. Z - vertical coordinate

MARKER MATRICES

The following number convention is used for the MAR = matrix system, which classifies points (or nodes) on the main grid system = (Refer to Figure).

- MAR = 0, points outside the region of interest.
- MAR = 1, point on the far y-boundary.
- MAR = 2, point on the near y-boundary.
- MAR = 3, point on the near x-boundary.
- MAR = 4, point on the far x-boundary.
- MAR = 5, outside corner on near x-boundary and far y-boundary.
- MAR = 6, inside corner on far x-boundary and far y-boundary.
- MAR = 7, outside corner on near x-boundary and near y-boundary.
- MAR = 8, inside corner on near x-boundary and near y-boundary.
- MAR = 9, outside corner on far x-boundary and near y-boundary.
- MAR = 10, outside corner on far x-boundary and far y-boundary.
- MAR = 11, points in the interior of the region of interest.

The following number convention is used to describe the MRH (matrix for the half-grid system).

MRH = 1, corner at far x-boundary and far y-boundary.

MRH = 2, points on near y-boundary.

MRH = 3, points on near x-boundary.

MRH = 4, corner at near x and near y-boundaries.

MRH = 6, far corner on x-axis.

MRH = 7, corner at far x and y-boundaries.

MRH = 9, interior grid points.

SECTION 5

PREPARATION OF RUNS

This section presents the steps to be followed in order to run the model for a particular location.

1. The boundaries are chosen depending on the particular situation, the general idea being to include all inflows and outflows. If a heated discharge enters the body of water the region of interest must be chosen so as to include this since it is a major factor in determining the size and spread of the resulting plume.
2. The grid size is chosen depending on the resolution required. The user should remember that the choice of the grid size directly determines the maximum allowable time step since this is directly related by the various stability criteria. (See choice of time step in Section 6.)
3. Specify number of full-grid points IN, JN, KN and number of half-grid points IWN, JWN. Since the actual domain may be smaller than the total rectangular region, INxJNxKN, the marker matrices MAR and MRH are used to specify the domain so that points outside the domain of interest skip the subsequent calculations.
4. IRUN is specified (= 0 for the first run, = 1 for subsequent runs). KSTORE is specified to indicate whether any tape has been assigned to store results of the run.

KSTORE = 0 if no tape has been assigned.

= 1 if tape has been assigned.

LLN is specified to denote the number of hours of simulation to be carried out.

5. The depths at various places within the domain are specified using subroutine HEIGHT. The various inflows and outflows to the domain are specified using INLET1. (For details please refer to Biscayne Bay run, Sengupta et al. (1975).)
6. The various data like solar radiation, wind speed, wind direction and dewpoint temperature are specified in a data file which is made by the main program.

For further details see the next section.

SECTION 6

INPUT DATA

The data that is required for the execution of the main program is listed in Table 3 in the order it appears. Note, the data input symbols have already been defined in Section 4. Moreover, the following remarks should be observed.

- * Free format is used for all data input.
- * Distinction must be made for integer and real number.
- * The order of the cards must be followed.

SECTION 7

PLOTTING PROGRAMS

The plotting programs for the 3-D rigid-lid model are distinct from the main program and subroutines used to run it. The user has an option of either using a tape (Unit 8) during running the main program TMAINN to store the results or just run it without storing the results. For making subsequent continuation runs of TMAINN all that is required is the result of the last hour in the previous run. For plotting, however, one needs the results of all the hours for which results are to be plotted. These results are used as input data to run the various plotting programs.

DESCRIPTION OF PLOT PROGRAMS

The following are the main plotting programs.

- PLOT - plots surface isotherms.
- PLUV - plots u, v components of the velocities (i.e., 'K' sections).
- PLUW - plots u, w components of the velocities (i.e., 'j' sections).
- PLVW - plots v, w components of the velocities (i.e., 'i' sections).

SUBROUTINES

The various plot programs and subroutines are shown in Table 4.

Other subroutines seen in these programs (e.g., ARROHD, FLINE, etc.) are standard FORTRAN subroutines used for plotting, using a CALCOMP x,y plotter, and are hence omitted in the above listing.

REFERENCES

- Lee, S., Sengupta, S., Nwadike, E. V. and S. K. Sinha. Verification of Three-Dimensional Rigid-Lid Model at Lake Keowee. Technical Report 1980, NASA Contract NAS10-9410.
- Sengupta, S., Lee, S. S. and R. Bland. Numerical Modeling of Circulation in Biscayne Bay. Transaction of the American Geophysical Union, June 1975.
- Sengupta, S. and W. Lick. A Numerical Model for Wind-Driven Circulation and Temperature Fields in Lakes and Ponds. FTAS/TR-74-98, 1974.
- Wilson, B. W. Note on Surface Wind Stresses Over Water at Low and High Wind Speeds. Journal of Geophysical Research, Vol. 65, No. 10, 1960.

APPENDICES

APPENDIX A

EXAMPLE CASE

INTRODUCTION

The area of interest is Lake Keowee in South Carolina, which was formed from 1968 through 1971 by damming the Little and Keowee rivers. The lake is located about 40 km west of Greenville and constitutes Duke Power Company's Keowee-Toxaway complex.

Lake Keowee has two arms connected by a canal (maximum depth 30.5 m). There are three power plants on the lake, namely, the Oconee Nuclear Station, Keowee hydro station and Jocassee-pumped storage station. The Oconee Nuclear Station is a three unit steam-electric station with an installed capacity of generating 2580 MW. The Oconee Nuclear Station draws in condenser-cooling water from the lower arm of Lake Keowee and discharges the heated effluent to the upper arm of the lake. The intake structure for the condenser-cooling water allows water from 20 to 27 m depth (full pond) to pass through. The discharge structure has an opening from 9 to 12 meters below the water surface (full pond) through which the CCW returns directly to the upper branch of the lake.

Lake Jocassee is located north of Lake Keowee and is used as a reservoir for Jocassee-pumped storage station. Lake Keowee also serves as the lower pond for this station. The Jocassee station has reversible turbines with a maximum generating flow (into Lake Keowee) of about 820 m³/sec and a maximum pumping flow (out of Lake Keowee into Lake Jocassee) of about 775 m³/sec, the net flow into Lake Keowee from Jocassee being about 15.5 m³/sec.

Lake Keowee has a full pond elevation of 243.8 m above MSL. At full pond it has a volume of approximately 1.18×10^9 m³, an area of 74 km², a mean depth of 15.8 m and a shoreline of about 480 km. The outflow from Lake Keowee is through Keowee hydro station and may vary from approximately 1.4 m³/sec (leakage) to 560 m³/sec. Maximum allowable draw-down of the lake is 7.6 m.

A map of the area of interest is shown in Figure 3.

PROBLEM STATEMENT

The objective of the present work is to find the three-dimensional temperature and velocity distributions in the region where the effects of the thermal discharge are noticeable. The effects of Jocassee-pumped

storage station, Keowee hydro station as well as the meteorological conditions have been incorporated.

The region of interest is chosen to include the effects of the Oconee Nuclear Station discharge, the outflow through Keowee dam and the impact of the Jocassee-pumped storage station on the velocity and temperature distributions in Lake Keowee. The depth of the domain is cut off at 16 meters, since this is the level at which the thermocline occurs. Hence, for running the model, a constant depth region is considered. The plan view of the domain is shown in Figure 4. (Note: For variable depth refer to Biscayne Bay simulation studies by the University of Miami thermal pollution group.) In this figure, AB is an open boundary which takes care of the flow from or to the Jocassee-pumped storage station. 'C' shows the position of the flow in the canal connecting the two arms of the lake. 'D' is the discharge point for the Oconee Nuclear Station and 'E' is the outflow from Keowee hydro station.

The inclusion of the above results in a domain 2895.6 m x 2438.4 m in the horizontal plane. The horizontal grid size (in x and y directions) is 152.4 m x 152.4 m, giving a total of 20 x 17 (= 340) nodes in the horizontal plane, out of which 293 lie in the region of interest. The 16 m constant depth region of interest is divided into 4 equal slices of 4 m each, giving a total of 5 nodes in the vertical (Z) direction. Hence, there are 293 x 5 nodes (grid points) in the region of interest. This region is specified using the MAR and MRH marker matrices (Figure 5 and Figure 6).

Boundary Conditions

On the Jocassee effect boundary, the flow velocity (varying with time) is specified. Open-boundary condition ($\frac{\partial T}{\partial y} = 0$) is specified for the temperature.

The same is done for the Keowee hydro boundary. The only difference is that the values specified are at three points in the vertical plane (i.e., at K = 1, 2 and 3) since this region covers the discharge area.

For the Oconee Nuclear Station, the discharge velocity as well as the discharge temperature is specified at the discharge point.

Open-boundary conditions are specified for the temperature and velocity at the canal. This, however, leads to a possible violation of mass balance in the region of interest. This mass unbalance will actually show up as a variation in the water level in the lake which is beyond the capability of the rigid-lid model.

At all solid boundaries as well as the artificial bottom (since the bottom is cut off at 16 m) perfect insulation (temperature gradient = 0) and zero velocity conditions are assumed.

At the surface, the vertical component of the velocity is specified

as zero (rigid-lid constraint). Surface wind shear stress and heat transfer coefficient are specified.

Initial Conditions

The initial values of the water velocities are assumed to be zero. The initial temperature of the lake is assumed to be equal to the ambient water temperature (determined by running a one-dimensional model) and is taken to be uniform throughout the domain.

CALCULATION OF PARAMETERS AND INPUT DATA

Reference Quantities

Reference length = L = maximum length of the domain = 2895.6 m.

Reference horizontal eddy viscosity $A_{ref} = 0.002 L^{4/3}$
 $= 38311.48 \text{ cm}^2/\text{sec}.$

For better agreement with data the value chosen is $60,000 \text{ cm}^2/\text{sec}.$

Reference depth = H = 16 m.

Reference vertical $A_v = 0.002 \times (H)^{4/3}.$

Eddy viscosity = $37.43 \text{ cm}^2/\text{sec}.$

Reference velocity = $V_{ref} = 30 \text{ cm/sec}.$


Reference temperature = $T_{ref} = 10.0^\circ\text{C}.$

Reference time = $L/V_{ref} = 9652 \text{ sec}.$

Calculation of Inflows and Outflows into the Domain (Used in INLET1)

Oconee Nuclear Station Discharge Velocity--

The discharge is considered to take place through a point at a depth of 12 m ($k = 3$). The discharge velocity is calculated as follows:



The total discharge into the basin is equal to:

$$\left(100 \frac{\text{cm}}{\text{m}} \times V \times 152.4 \times 12\right) = Q$$

where Q = average discharge in m^3/sec

$$\therefore V = \frac{8144.1}{60} \text{ m/sec}$$

$$= 7.42207 \text{ cm/sec}$$

The average values of Q over 24 hrs is taken since the variation is negligible.

$$\text{Nondimensional discharge velocity} = \frac{V}{V_{\text{ref}}} = \frac{V}{30} = 0.24740$$

Keowee Hydro Discharge Velocity--

The outflow through the Keowee hydro station is through a channel $152.4 \text{ m} \times 12 \text{ m}$.

$$\text{The volume flowrate } Q = (152.4 \times 12 \times V) \text{ m}^3/\text{sec}$$

where V = discharge velocity (m/sec)


$$\therefore V = [Q / (152.4 \times 12)] \text{ m/sec} = \left(\frac{Q}{152.4 \times 12 \times 100} \right) \text{ cm/sec}$$

Q is specified as a function of time in INLET1.

The procedure for nondimensionalization is similar.

Jocassee Flow Velocity--

The entire flow to or from the Jocassee-pumped storage station is assumed to take place through the entire upper boundary (AB in Figure 4). The flow through this area (shown below) is assumed to be uniform and is assumed to take place simultaneously with the outflow through the Jocassee station.



$$V = Q / [(16 \times 13 \times 152.4) \times 100] \text{ cm/sec.}$$

Q = flow through Jocassee (m^3/sec).

Q is positive when Jocassee is generating (i.e., the flow is into the region of interest) and negative when pumping (i.e., flow out of region of interest).

SAMPLE INPUT

The following are the inputs to TMAINN contained in the data file IPUT (which includes values calculated earlier).

Input #	No. of Data In Card	Symbol	Value
1	3	IRUN	= 0
		KSTORE	= 1
		LLN	= 3
2	2	VVIS	= $37.43/60,000 = 0.00062384$
		ABR	= 0.78
3	4	AI	= 1.0
		AH	= $\frac{60,000}{30 \times 2895 \times 100} = 0.01228172$
		AV	= $(\frac{2895.6^2}{16})$ AH = 402.08304
		AP	= 1.0
4	4	EPS	= 0.001
		MAXIT	= 60
		OMEGA	= 1.8
		ARBP	= 1.0
5	3	DX	= $152.4/2895.6 = 0.05263$
		DY	= 0.05263
		DZ	= $4/16 = 0.25$
6	3	TAI	= 1.0
		TAH	= AH = 0.01228172
		TAV	= AV = 402.08304
7	3	A	= 1.000428
		B	= -0.000019

Input #	No. of Data In Card	Symbol	Value
		C	= -0.0000046
8	1	TO	= 10.0
9	3	EUL	= $\frac{980 \times (16 \times 100)}{30^2} = 1742.222$
		CW	= 0.0
		CB	= 0.0
10	2	AA	= 0.24740
		CC	= 16/16 = 1.0
11	1	TLL	= $\frac{31.7 - 10}{10}$
12	1	TAU	= 0.0152 cm ² /sec
13	1	DT	Criterion (convective) $= \Delta t < \frac{\Delta x}{U} = \frac{152.4 \times 100}{30}$ $= 504 \text{ secs} > 504 \text{ secs}$ Hence, convective criterion dominates; choose $\Delta T = 300 \text{ secs}$ $DT = \frac{\Delta T}{t_{ref}} = \frac{300}{9652} = 0.03108164$ Note: choose best time step by trial and error
14	1	CTTOT	= $t_{ref}/3600 = 2.6811111$
15	1	ISOTOP	= 0
16	6	WS	
		TSU	
		TDEW	
		RADN	See Table 5
		ISGNX	
		ISGNY	
17	1	ANGLE	See Table 5

LAKE KEOWEE APPLICATION-EXECUTION DECK

The following execution deck is for use in the UNIVAC 1100 computer at the University of Miami. These may have to be modified if a different computer is used.

(ALL PROGRAMS AND SUBPROGRAMS COMPILED AND STORED IN FILE)

First Run

1. @ ASG, AX FILE.
(THE FILE IS ASSIGNED FOR THE RUN)
2. @ ASG,T 8, 16N, TAPENAME.
(A TAPE FILE NAMES '8' IS BEING ASSIGNED. THE TAPE IS 9-TRACK, AND THE REEL NUMBER IS 'TAPENAME')
3. @ PRT,S FILE. TMAINN
(THE MAIN PROGRAM IS PRINTED)
4. @ PACK FILE.
(THE FILE IS PACKED)
5. @ PREP FILE.
(ENTRY POINT TABLE IS PREPARED)
6. @ MAP,S
7. IN FILE. TMAINN
8. LIB FILE.
9. END
10. @ XQT
11. 0
(VALUE FOR IRUN,FIRST RUN: IRUN=0)
12. 24
(NUMBER OF HOURS REQUIRED, MINIMUM=1 HOUR, MAX=24)

13. 0

(0 IF MAGNETIC TAPE IS REQUIRED TO STORE RESULT, IF
NOT, ANY NUMBER)

14. @ ADD FILE. INPUT

(INPUT DATA FILE FOR THE PARTICULAR RUN)

15. @ FIN

EXECUTION DECK FOR PLOT PROGRAMS

1. @ ASG,AX FILE.

2. @ ASG,T 8., 16N, TAPENAME.

3. @ ASG,T 11., 16N, PLOTTAPE.

(A MAGNETIC TAPE FILE NAMED '11' IS BEING ASSIGNED. THE
TAPE IS 7-TRACK AND THE REEL NUMBER IS 'PLOTTAPE'. THE
PLOTS ARE STORED ON THIS TAPE)

4. @ PRT,S FILE.PLOTTER

(THE PLOT PROGRAM IS PRINTED)

5. @ PACK FILE.

6. @ PREP FILE.

7. @ MAP,S

8. IN FILE.PLOTTER

9. LIB FILE.

10. END

11. @ XQT

12. @ ADD FILE. INPUT

13. @ FIN

Table 2. Subroutines Required in Main Program TMAINN

No.	Name	Description	Remarks
1	DVISV	Computes DIVY, D2VY, D1VX and D2VX.	Called by subroutine INTE. Schemes used similar to DVISU.
2	DVISU	Computes D1UX, D2UX, and D1UY.	Called by INTE. $\frac{\partial u}{\partial x}, \frac{\partial u}{\partial y}$ are computed at interior, boundary or corner pts by scheme similar to the one used in DINERU.
3	DVVY	Computes D1HVVY.	Called by INTE. $\frac{\partial}{\partial y}$ (hvv) is computed for interior, boundary or corner by a scheme similar to the one used in DINERU.
4	DUVY	Computes D1HUVY.	Called by INTE. $\frac{\partial}{\partial y}$ (huv) is computed for interior, boundary and corner pts by a scheme similar to the one used in DINERU.
5	DINERU	Computes D1HUUX and D1HUVX.	Called by INTE. The results are used in Poisson equation for pressure.
6	TPRINK	Prints temperatures at a grid point.	Called by TMAINN.
7	PRUV	Prints the values of U and V at all main grid points.	Called by TMAINN.
8	PRITEX	Prints the No. of iterations (ITN) and final residual error in solving the Poisson equation	Called by TMAINN.
9	TPRIN1	Prints the input parameters.	Called by TMAINN.
10	STORE2	Stores values of input parameters and physical quantities on tape #8	Called by TMAINN.
11	RWR	Computes real vertical velocities from modified vertical velocities used in equations at integral grid points.	Called by TMAINN.

Table 2. Subroutines Required in Main Program TMAINN (Continued)

No.	Name	Description	Remarks
12	RWRH	Computes real vertical velocities at half-grid points.	Called by TMAINN.
13	DENSTY	Uses the equation of state and computes density field from the temperature field.	Called by TMAINN.
14	TEQB	Allows for vertical mixing at a particular grid point. Program is called by TMAINN.	If the temp at the grid pt just above it is less and the difference is more than a specified maximum, the two temperatures are averaged.
15	OLDT	Sets the values of temperature field at time step 'n' equal to the temperature field at (n+1) after all computations for time step 'n' are completed.	
16	TEMB2	Computes temperatures at the boundary points in the domain of interest.	Called by TMAINN.
17	TEMI4	Computes temperatures at the interior points of the domain of interest.	Called by TMAINN.
18	RWH	Computes vertical velocities at half-grid points.	Called by TMAINN.
19	OLDUV	Sets the values of D and E equal to U and V respectively in order to retain values of U and V at one time step lag.	Called by TMAINN.
20	UVTOP	Computes U and V at the top using wind stress boundary conditions.	Called by TMAINN. Computations are made for MAR = 11 only (internal grid points).
21	UVT	Computes U and V for variable density at successive time steps.	Called by TMAINN.

Table 2. Subroutines Required in Main Program TMAINN (Continued)

No.	Name	Description	Remarks
22	PRE1L	Computes pressure for far field from Poisson's Equation at half-grid points.	Called by TMAINN.
23	FORCE	Computes R.H.S. of Poisson's Equation at half-grid points.	Called by TMAINN.
24	DPSXY	Computes DPSX and DPSY.	Called by TMAINN.
25	ROINTY	Computes Y_p in the Poisson's Equation.	Called by TMAINN.
26	ROINTX	Computes X_p in the Poisson's Equation.	Called by TMAINN.
27	CORINT	Adds integral of Coriolis' component XINT and YINT.	Called by TMAINN.
28	INTE	Computes XINT, YINT, DPSX, and DPSY.	Called by INTE.
29	WHATIJ	Computes the values of W at I, J from the values of WH at IW, JW.	Called by TMAINN.
30	WHTOP	Sets the value of WH equal to zero at the surface.	Called by TMAINN.
31	ERROR	Calculates "Hirt and Harlow" correction term at half-grid points and at the surface (WHLDT).	Called by TMAINN.
32	READ2	Reads in input parameters and physical quantities stored on tape #7.	Corresponds to store 2. Called in by TMAINN.
33	INLET1	Puts in velocities u and v pheme discharge, etc. into the model.	Called by TMAINN.
34	HEIGHT	Inputs depths of the basin into the model.	This subroutine is for a constant depths model. Called by TMAINN.

Table 2. Subroutines Required in Main Program TMAINN (Continued)

No.	Name	Description	Remarks
35	INITIT	Sets initial temperature field.	Sets the temperature field equal to ref temp at all grid points. Called by TMAINN.
36	INITIA	Initializes values of U, V, WH, W, \bar{D} , E and PINTH.	Called by TMAINN.
37	READ 3K	Classifies region of interest into interior, corner and boundary points using matrix MAR.	Called by TMAINN.
38	IPUT	Data files containing values of input data for the respective days.	




Figure 1. Flow chart (main program)




Figure 1 (Continued). Flow chart (main program)




Figure 2. Coordinate and grid system

Table 3. Input Data to TMAINN

Input #	No. of Data In Card	Symbol	Definition/Value
1	3	IRUN	= 0 for first run
		LLN	= No of hours of simulation
		KSTORE	= 0 if no tape is assigned = 1 if tape is assigned
2	2	VVIS	= Nondimensional vertical eddy viscosity
		ABR	= 1/Rossby No. = $\frac{fL}{U_{ref}}$
3	4	AI	= Coefficient in front of inertia term = 1.0
		AH	= 1/Reynolds No. = $\frac{\text{Ref eddy hoz viscosity}}{U_{ref} \cdot L}$
	4	AV	= $(1/\epsilon^2 Re)$ ($\epsilon = H/L$)
		AP	= Coefficient in front of pressure term = 1.0
4	4	EPS	= Convergence factor = 0.001
		MAXIT	= Maximum number of iterations for Poisson Equation
		OMEGA	= Relaxation factor = 1.8
		ARBP	= Arbitrary pressure = 1.0
5	3	DX	= Horizontal grid spacing (x dir.)
		DY	= Horizontal grid spacing (y dir.) = $\Delta y/L$
		DZ	= Vertical grid spacing (z dir.) = $\Delta z/H$
6	3	TAI	= Coefficient of convective terms in energy equation = 1.0
		TAH	= Horizontal eddy diffusivity = AH (usually)

Table 3. Input Data to TMAINN (Continued)

Input #	No. of Data In Card	Symbol	Definition/Value
		TAV	= Vertical eddy diffusivity = AV (usually)
7	3	A	= 1.000428 These are coefficients = -0.000019 in the equation of = -0.0000046 state for water where $\rho = A + BT + CT^2$ (gm/cc)
8	1	TO	= Reference temperature (°C)
9	3	EUL	= Euler No. = $\frac{gH}{(U_{ref})^2}$
		CW	= Temperature gradient at vertical boundary
		CB	= Temperature gradient at the bottom
10	2	AA	= Nondimensional discharge velocity = (discharge velocity) / U_{ref}
		CC	= No dimensional depth = h/H_{ref}
11	1	TLL	= Nondimensional discharge temperature = $(T_D - T_o) / T_o$
12	1	TAU	= Surface shear stress (from Wilson Curve) (Refer to Figure 7)
13	1	DT	= Nondimensional time step = $\Delta T(L/U_{ref})$
14	1	CTTOT	= Converts nondimensional time to hours
15	1	ISTOP	= Number of hours of previous run
16	6	WS	= Wind speed (m/sec)
		TSU	= Air temperature (°C)
		TDEW	= Dewpoint temperature (°C)
		RADN	= Incident solar radiation (w/m ²)

Table 3. Input Data to TMAINN (Continued)

Input #	No. of Data In Card	Symbol	Definition/Value
		ISGNX	= +1 if x component of W_s is negative = -1 if x component of W_s is positive = +1 if y component of W_s is negative = -1 if y component of W_s is positive
17	1	ANGLE	= Direction of W_s (degrees) with respect to the s_x axis

Table 4. Plotting Programs

No.	Name	Program Description	Remarks
1	PLOT	Plots surface isotherms	
2	PLUV	Plots velocities, K section	
3	PLUW	Plots velocities, j section	
4	PLVW	Plots velocities, i section	
5	ECHKON	Calculates equal temperature points	Called by PLOT
6	CONLIN	Draws the isotherms	Called by ECHKON
7	ENDER	Writes the values of the temperature on the isotherms	Called by ECHKON




Figure 3. Lake Keowee




Figure 4. Lake Keowee (region of interest) showing Inputs and outputs (for 3-D model)

1	0	0	0	0	0	0	7	3	3	7	3	3	3	3	3	3	3	3	5
2	0	0	0	0	0	0	2	11	11	11	11	11	11	11	11	11	11	11	1
3	0	0	0	0	7	7	3	11	11	11	11	11	11	11	11	11	6	2	10
4	0	0	0	0	2	11	11	11	11	11	11	11	11	11	11	11	1	0	0
5	0	0	0	0	9	3	11	11	11	11	11	11	11	11	11	11	1	0	0
6	0	0	0	0	0	2	11	11	11	11	11	11	11	11	11	11	6	2	3
7	0	0	7	3	3	5	11	11	11	11	11	11	11	11	11	11	11	11	1
8	0	0	2	11	11	11	11	11	11	11	11	11	11	11	11	11	6	8	10
9	0	0	2	11	11	11	11	11	11	11	11	11	11	11	11	11	6	10	2
10	7	3	5	11	11	11	11	11	11	11	11	11	11	11	11	11	1	0	9
11	2	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	6	3	5
12	9	2	2	2	2	5	11	11	11	11	6	2	3	11	11	11	1	0	0
13	0	0	0	0	0	9	2	3	11	11	1	0	2	11	11	11	1	0	0
14	0	0	0	0	0	0	0	2	11	6	10	0	9	3	11	11	6	5	0
15	0	0	0	0	0	0	0	2	11	1	0	0	0	2	11	11	11	1	0
16	0	0	0	0	0	0	0	2	11	1	0	0	0	9	2	2	2	10	0
17	0	0	0	0	0	0	0	9	4	10	0	0	0	0	0	0	0	0	0

Figure 5. MAR marker matrix

1	0	0	0	0	0	0	4	10	10	10	10	10	10	10	10	10	10	10
2	0	0	0	0	0	0	2	9	9	9	9	9	9	9	9	9	9	7
3	0	0	0	0	0	4	10	9	9	9	9	9	9	9	9	9	1	0
4	0	0	0	0	0	6	9	9	9	9	9	9	9	9	9	9	1	0
5	0	0	0	0	0	2	9	9	9	9	9	9	9	9	9	9	1	0
6	0	0	0	0	0	2	9	9	9	9	9	9	9	9	9	9	10	10
7	0	0	-	10	10	9	9	9	9	9	9	9	9	9	9	9	3	9
8	0	0	2	9	9	9	9	9	9	9	9	9	9	9	9	7	0	2
9	0	0	2	9	9	9	9	9	9	9	9	9	9	9	1	0	0	6
10	-	10	9	9	9	9	9	9	9	9	9	9	9	9	1	0	0	0
11	0	3	3	3	3	9	9	9	9	9	3	3	9	9	10	3	0	0
12	0	0	0	0	0	6	3	9	9	1	0	0	2	9	9	1	0	0
13	0	0	0	0	0	0	2	9	9	0	0	0	6	9	9	1	0	0
14	0	0	0	0	0	0	2	1	0	0	0	0	0	2	9	9	0	0
15	0	0	0	0	0	0	2	1	0	0	0	0	0	9	3	3	7	0
16	0	0	0	0	0	0	0	6	7	0	0	0	0	0	0	0	0	0

Figure 6. MRH marker matrix

Table 5. Meteorological Data for Lake Keowee (February 27, 1979)

Time (hrs from midnight)	Wind Speed (m/s)	Air Temp (°C)	Dewpoint Temp (°C)	Solar Radiation (w/m ²)	Wind Direction (Degrees)
1	1.833	-0.33	-2.78	0.0	15°
2	1.073	-0.72	-1.67	0.0	75°
3	2.325	-1.61	-1.61	0.0	60°
4	1.565	-2.22	-2.28	0.0	15°
5	2.056	-1.83	-1.89	0.0	50°
6	1.788	-2.17	-2.22	0.0	85°
7	2.012	-2.72	-2.78	20.94	85°
8	2.280	-1.67	-2.78	195.39	60°
9	0.626	0.01	-3.33	369.85	5°
10	1.386	3.06	-2.22	544.31	75°
11	1.609	5.83	-2.22	655.31	15°
12	1.788	8.83	-1.39	725.75	40°
13	3.129	11.06	-2.78	746.68	80°
14	2.593	12.28	-5.00	704.81	70°
15	1.520	13.39	-5.56	579.20	80°
16	1.207	13.89	-5.56	383.81	75°
17	1.565	13.83	-5.61	146.55	55°
18	1.609	13.72	-3.33	20.94	15°
19	2.056	11.72	-4.44	0.0	30°
20	1.162	9.72	-2.78	0.0	25°
21	1.772	8.33	5.28	0.0	55°
22	2.861	7.78	5.56	0.0	55°
23	2.995	7.00	5.28	0.0	50°
24	1.386	5.28	3.89	0.0	60°

Table 6. Inflows and Outflows to Lake Keowee

Time Feb. 27, 1978	Oconee Discharge (m ³ /min)	Oconee Discharge Temp (°C)	Net Jocassee Flow (C.F.S.)	Keowee Hydro Flow (C.F.S.)
12.00 a.m.	7505.3	18.6	-14395	48
1.00	7498.1	18.5	-18754	48
2.00	7492.0	18.4	-18805	48
3.00	7492.0	18.5	-18713	48
4.00	7491.6	18.3	-18698	48
5.00	7494.3	18.3	-18688	48
6.00	7488.2	18.3	-15939	48
7.00	7481.8	18.2	3484	3668
8.00	7485.6	18.3	16823	17540
9.00	7488.2	18.2	13503	8488
10.00	7497.7	18.3	5470	8096
11.00	7504.1	18.3	100	2680
12.00 p.m.	7503.4	18.4	100	48
1.00	7506.0	18.5	100	48
2.00	7506.4	18.5	100	48
3.00	7503.4	18.4	100	48
4.00	7501.9	18.4	100	48
5.00	7507.5	18.4	100	48
6.00	7511.0	18.4	100	48
7.00	7516.2	18.4	100	48
8.00	7518.9	18.3	100	48
9.00	7520.4	18.2	100	48
10.00	7516.6	18.2	100	48
11.00	7509.4	18.2	100	48
12.00 a.m.	7507.2	18.2	-4382	48




Figure 7. Keowee hydro discharge (February 27, 1979)




Figure 8. Jocassee-pumped storage station discharge data (February 27, 1979)

APPENDIX B
FORTRAN SOURCE PROGRAM LISTING

LIST OF MAIN PROGRAM AND SUBROUTINES


```

1      ASA*HASA111,CORINT FOR CREATED ON 5 MAY 90 AT 10:49:16
2      C.....
3      C THIS SUBROUTINE ADDS INTEGRAL OF CORIOLIS COMPONENT TO XINT
4      C C VINT.
5      C.....
6      SUBROUTINE CORINT(I,J,A,IN,UN,AN,ABR,U,V,XINT,VINT,DT,HI,TA,I
7      DIMENSION U(IN,UN,ANI,V(IN,UN,ANI,XINT(IN,UNI,VINT(IN,UNI,HI(I
8      C*J,AN,IN,UN)
9      DO 10 I=1,IN
10     DO 10 J=1,UN
11     IF (VARI(I,J).LT.111) GO TO 9
12     DO 3 K=2,AN
13     XINT(I,J)=XINT(I,J)+ABR*HI(I,J)*U(I,J,AN-1)*V(I,J,AN)*DT/2
14     VINT(I,J)=VINT(I,J)+ABR*HI(I,J)*U(I,J,AN-1)*V(I,J,AN)*DT/2
15     CONTINUE
16     CONTINUE
17     RETURN
18     END

```



```

10 40 CONTINUE
11 61=0.01*(1+M111,01*011,0,01*011,0,01*011-1,01*011-1,0,01
12 62=0.01*(1+M111,01*011-2,01*011-2,0,01*011-2,0,01*011-2,0,01
13 63=0.01*(1+M111,01*011,0,01*011-2,01*011-2,0,01*011-2,0,01
14 64=0.01*(1+M111,01*011,0,01*011-2,01*011-2,0,01*011-2,0,01
15 65=0.01*(1+M111,01*011-2,01*011-2,0,01*011-2,0,01*011-2,0,01
16 50 CONTINUE
17 RETURN
18 END

```


0200, 0100, 0300, 0400, 0500, 0600, 0700, 0800, 0900, 1000, 1100, 1200, 1300, 1400, 1500, 1600, 1700, 1800, 1900, 2000, 2100, 2200, 2300, 2400, 2500, 2600, 2700, 2800, 2900, 3000, 3100, 3200, 3300, 3400, 3500, 3600, 3700, 3800, 3900, 4000, 4100, 4200, 4300, 4400, 4500, 4600, 4700, 4800, 4900, 5000, 5100, 5200, 5300, 5400, 5500, 5600, 5700, 5800, 5900, 6000, 6100, 6200, 6300, 6400, 6500, 6600, 6700, 6800, 6900, 7000, 7100, 7200, 7300, 7400, 7500, 7600, 7700, 7800, 7900, 8000, 8100, 8200, 8300, 8400, 8500, 8600, 8700, 8800, 8900, 9000, 9100, 9200, 9300, 9400, 9500, 9600, 9700, 9800, 9900, 10000, 10100, 10200, 10300, 10400, 10500, 10600, 10700, 10800, 10900, 11000, 11100, 11200, 11300, 11400, 11500, 11600, 11700, 11800, 11900, 12000, 12100, 12200, 12300, 12400, 12500, 12600, 12700, 12800, 12900, 13000, 13100, 13200, 13300, 13400, 13500, 13600, 13700, 13800, 13900, 14000, 14100, 14200, 14300, 14400, 14500, 14600, 14700, 14800, 14900, 15000, 15100, 15200, 15300, 15400, 15500, 15600, 15700, 15800, 15900, 16000, 16100, 16200, 16300, 16400, 16500, 16600, 16700, 16800, 16900, 17000, 17100, 17200, 17300, 17400, 17500, 17600, 17700, 17800, 17900, 18000, 18100, 18200, 18300, 18400, 18500, 18600, 18700, 18800, 18900, 19000, 19100, 19200, 19300, 19400, 19500, 19600, 19700, 19800, 19900, 20000, 20100, 20200, 20300, 20400, 20500, 20600, 20700, 20800, 20900, 21000, 21100, 21200, 21300, 21400, 21500, 21600, 21700, 21800, 21900, 22000, 22100, 22200, 22300, 22400, 22500, 22600, 22700, 22800, 22900, 23000, 23100, 23200, 23300, 23400, 23500, 23600, 23700, 23800, 23900, 24000, 24100, 24200, 24300, 24400, 24500, 24600, 24700, 24800, 24900, 25000, 25100, 25200, 25300, 25400, 25500, 25600, 25700, 25800, 25900, 26000, 26100, 26200, 26300, 26400, 26500, 26600, 26700, 26800, 26900, 27000, 27100, 27200, 27300, 27400, 27500, 27600, 27700, 27800, 27900, 28000, 28100, 28200, 28300, 28400, 28500, 28600, 28700, 28800, 28900, 29000, 29100, 29200, 29300, 29400, 29500, 29600, 29700, 29800, 29900, 30000, 30100, 30200, 30300, 30400, 30500, 30600, 30700, 30800, 30900, 31000, 31100, 31200, 31300, 31400, 31500, 31600, 31700, 31800, 31900, 32000, 32100, 32200, 32300, 32400, 32500, 32600, 32700, 32800, 32900, 33000, 33100, 33200, 33300, 33400, 33500, 33600, 33700, 33800, 33900, 34000, 34100, 34200, 34300, 34400, 34500, 34600, 34700, 34800, 34900, 35000, 35100, 35200, 35300, 35400, 35500, 35600, 35700, 35800, 35900, 36000, 36100, 36200, 36300, 36400, 36500, 36600, 36700, 36800, 36900, 37000, 37100, 37200, 37300, 37400, 37500, 37600, 37700, 37800, 37900, 38000, 38100, 38200, 38300, 38400, 38500, 38600, 38700, 38800, 38900, 39000, 39100, 39200, 39300, 39400, 39500, 39600, 39700, 39800, 39900, 40000, 40100, 40200, 40300, 40400, 40500, 40600, 40700, 40800, 40900, 41000, 41100, 41200, 41300, 41400, 41500, 41600, 41700, 41800, 41900, 42000, 42100, 42200, 42300, 42400, 42500, 42600, 42700, 42800, 42900, 43000, 43100, 43200, 43300, 43400, 43500, 43600, 43700, 43800, 43900, 44000, 44100, 44200, 44300, 44400, 44500, 44600, 44700, 44800, 44900, 45000, 45100, 45200, 45300, 45400, 45500, 45600, 45700, 45800, 45900, 46000, 46100, 46200, 46300, 46400, 46500, 46600, 46700, 46800, 46900, 47000, 47100, 47200, 47300, 47400, 47500, 47600, 47700, 47800, 47900, 48000, 48100, 48200, 48300, 48400, 48500, 48600, 48700, 48800, 48900, 49000, 49100, 49200, 49300, 49400, 49500, 49600, 49700, 49800, 49900, 50000, 50100, 50200, 50300, 50400, 50500, 50600, 50700, 50800, 50900, 51000, 51100, 51200, 51300, 51400, 51500, 51600, 51700, 51800, 51900, 52000, 52100, 52200, 52300, 52400, 52500, 52600, 52700, 52800, 52900, 53000, 53100, 53200, 53300, 53400, 53500, 53600, 53700, 53800, 53900, 54000, 54100, 54200, 54300, 54400, 54500, 54600, 54700, 54800, 54900, 55000, 55100, 55200, 55300, 55400, 55500, 55600, 55700, 55800, 55900, 56000, 56100, 56200, 56300, 56400, 56500, 56600, 56700, 56800, 56900, 57000, 57100, 57200, 57300, 57400, 57500, 57600, 57700, 57800, 57900, 58000, 58100, 58200, 58300, 58400, 58500, 58600, 58700, 58800, 58900, 59000, 59100, 59200, 59300, 59400, 59500, 59600, 59700, 59800, 59900,

DIMENSION: U(1),U(1),SU(2),SU(2),SU(2),SU(2)

57

210

1
 2
 3
 4
 5
 6
 7
 8
 9
 10
 11
 12
 13
 14
 15
 16
 17
 18
 19
 20
 21
 22
 23
 24
 25
 26
 27
 28
 29
 30
 31
 32
 33
 34
 35
 36
 37
 38
 39
 40
 41
 42
 43
 44
 45
 46
 47
 48
 49
 50
 51
 52
 53
 54
 55
 56
 57
 58
 59
 60
 61
 62
 63
 64
 65
 66
 67
 68
 69
 70
 71
 72
 73
 74
 75
 76
 77
 78
 79
 80
 81
 82
 83
 84
 85
 86
 87
 88
 89
 90
 91
 92
 93
 94
 95
 96
 97
 98
 99
 100
 101
 102
 103
 104
 105
 106
 107
 108
 109
 110
 111
 112
 113
 114
 115
 116
 117
 118
 119
 120
 121
 122
 123
 124
 125
 126
 127
 128
 129
 130
 131
 132
 133
 134
 135
 136
 137
 138
 139
 140
 141
 142
 143
 144
 145
 146
 147
 148
 149
 150
 151
 152
 153
 154
 155
 156
 157
 158
 159
 160
 161
 162
 163
 164
 165
 166
 167
 168
 169
 170
 171
 172
 173
 174
 175
 176
 177
 178
 179
 180
 181
 182
 183
 184
 185
 186
 187
 188
 189
 190
 191
 192
 193
 194
 195
 196
 197
 198
 199
 200
 201
 202
 203
 204
 205
 206
 207
 208
 209
 210
 211
 212
 213
 214
 215
 216
 217
 218
 219
 220
 221
 222
 223
 224
 225
 226
 227
 228
 229
 230
 231
 232
 233
 234
 235
 236
 237
 238
 239
 240
 241
 242
 243
 244
 245
 246
 247
 248
 249
 250
 251
 252
 253
 254
 255
 256
 257
 258
 259
 260
 261
 262
 263
 264
 265
 266
 267
 268
 269
 270
 271
 272
 273
 274
 275
 276
 277
 278
 279
 280
 281
 282
 283
 284
 285
 286
 287
 288
 289
 290
 291
 292
 293
 294
 295
 296
 297
 298
 299
 300
 301
 302
 303
 304
 305
 306
 307
 308
 309
 310
 311
 312
 313
 314
 315
 316
 317
 318
 319
 320
 321
 322
 323
 324
 325
 326
 327
 328
 329
 330
 331
 332
 333
 334
 335
 336
 337
 338
 339
 340
 341
 342
 343
 344
 345
 346
 347
 348
 349
 350
 351
 352
 353
 354
 355
 356
 357
 358
 359
 360
 361
 362
 363
 364
 365
 366
 367
 368
 369
 370
 371
 372
 373
 374
 375
 376
 377
 378
 379
 380
 381
 382
 383
 384
 385
 386
 387
 388
 389
 390
 391
 392
 393
 394
 395
 396
 397
 398
 399
 400
 401
 402
 403
 404
 405
 406
 407
 408
 409
 410
 411
 412
 413
 414
 415
 416
 417
 418
 419
 420
 421
 422
 423
 424
 425
 426
 427
 428
 429
 430
 431
 432
 433
 434
 435
 436
 437
 438
 439
 440
 441
 442
 443
 444
 445
 446
 447
 448
 449
 450
 451
 452
 453
 454
 455
 456
 457
 458
 459
 460
 461
 462
 463
 464
 465
 466
 467
 468
 469
 470
 471
 472
 473
 474
 475
 476
 477
 478
 479
 480
 481
 482
 483
 484
 485
 486
 487
 488
 489
 490
 491
 492
 493
 494
 495
 496
 497
 498
 499
 500
 501
 502
 503
 504
 505
 506
 507
 508
 509
 510
 511
 512
 513
 514
 515
 516
 517
 518
 519
 520
 521
 522
 523
 524
 525

```
THIS SUBROUTINE COMPUTES J1VY,DZVY,D1VX & DZVX *
```

214145(04 JUL 14, 04, 04), 214146(04 JUL 14, 04), 214147(04 JUL 14, 04)

43

SC

001	171
002	172
003	173
004	174
005	175
006	176
007	177
008	178
009	179
010	180
011	181
012	182
013	183
014	184
015	185
016	186
017	187
018	188
019	189
020	190
021	191
022	192
023	193
024	194
025	195
026	196
027	197
028	198
029	199
030	200
031	201
032	202
033	203
034	204
035	205
036	206
037	207
038	208
039	209
040	210
041	211
042	212
043	213
044	214
045	215
046	216
047	217
048	218
049	219
050	220
051	221
052	222
053	223
054	224
055	225
056	226
057	227
058	228
059	229
060	230
061	231
062	232
063	233
064	234
065	235
066	236
067	237
068	238
069	239
070	240
071	241
072	242
073	243
074	244
075	245
076	246
077	247
078	248
079	249
080	250
081	251
082	252
083	253
084	254
085	255
086	256
087	257
088	258
089	259
090	260
091	261
092	262
093	263
094	264
095	265
096	266
097	267
098	268
099	269
100	270
101	271
102	272
103	273
104	274
105	275
106	276
107	277
108	278
109	279
110	280
111	281
112	282
113	283
114	284
115	285
116	286
117	287
118	288
119	289
120	290
121	291
122	292
123	293
124	294
125	295
126	296
127	297
128	298
129	299
130	300
131	301
132	302
133	303
134	304
135	305
136	306
137	307
138	308
139	309
140	310
141	311
142	312
143	313
144	314
145	315
146	316
147	317
148	318
149	319
150	320
151	321
152	322
153	323
154	324
155	325
156	326
157	327
158	328
159	329
160	330
161	331
162	332
163	333
164	334
165	335
166	336
167	337
168	338
169	339
170	340
171	341
172	342
173	343
174	344
175	345
176	346
177	347
178	348
179	349
180	350
181	351
182	352
183	353
184	354
185	355
186	356
187	357
188	358
189	359
190	360
191	361
192	362
193	363
194	364
195	365</


```

*****INLET1 ELT CREATED ON 5 MAY 80 AT 11:34:12*****
C*****
C      THIS SUBROUTINE FOR INLET AND OUTLETS FOR
C      JOM414
C*****
C      SUBROUTINE INLET1(I,J,A,IN,JN,AN,U,V,M,G,T,TO,AA,TLL,DT,HTTOT1)
C      DIMENSION M(14,JN,ANI),G(14,JN,ANI),U(14,JN,ANI)
C      DIMENSION V(14,JN,ANI),T(14,JN,ANI),TO(14,JN,ANI)
C      TSOT=HTTOT1
C      TSOT1=HTTOT1
C
C      COMMENT : THIS PROGRAM HAS BEEN WRITTEN SPECIFICALLY FOR
C      : LAKE PEDWEE. USERS MUST CHANGE TO SUIT SPECIFIC
C      : SITE. WATCH OUT FOR COMMENTS TO START OR STOP
C      : CHANGE.
C
C      JNM1=JN-1
C      JNM2=JN-1
C
C      COMMENT : START CHANGE.
C
C      M(1,1,1)=AA
C      G(1,1,1)=AA
C      H(1,1,1)=0.0
C      T(1,1,1)=TLL
C      TO(1,1,1)=TLL
C
C      IC
C      CONTINUE
C      SF=0.00322579
C      V(1,1,1)=1592653
C      AUCSE=0.54725
C      PUCSE=11.4545
C      IF(TSOT.LE.0.0.AND.TSOT.LE.1.0)SF=SF*1-14.395-(16.75-14
C      C.395)*TSOT1
C      IF(TSOT.LE.1.0.AND.TSOT.LE.5.0)SF=SF*1-19.7541
C      IF(TSOT.LE.5.0.AND.TSOT.LE.8.0)SF=SF*1-1116.823*
C      C(18.7541/7.19)*TSOT-5.01-19.7541
C      IF(TSOT.LE.8.0.AND.TSOT.LE.11.0)SF=SF*1-1116.823-
C      C(11.73-8.0)*TSOT-19.8231
C      IF(TSOT.LE.11.0.AND.TSOT.LE.23.0)SF=SF*0.1
C      IF(TSOT.LE.23.0.AND.TSOT.LE.24.0)SF=SF*1-14.5*0.111
C      C(TSOT-23.0)
C
C      COMMENT : STOP CHANGE.
C
C      DO 20 J=1,JNM1
C      DO 30 J=1,JNM1
C      U(1,J,1)=SV
C      H(1,J,1)=SV
C      V(1,J,1)=0.0
C      T(1,J,1)=TLL
C      TO(1,J,1)=TLL
C      TSOT1=TSOT
C      CONTINUE
C      TSOT=TSOT1
C      JNM1=JN-1
C
C      COMMENT : START CHANGE.
C
C      U(17,5,1)=2.0*U(18,5,1)-U(19,5,1)
C      H(17,5,1)=2.0*H(18,5,1)-U(19,5,1)
C      V(17,5,1)=0.0
C      T(17,5,1)=0.0
C
C      COMMENT : STOP CHANGE.
C
C      IC
C      CONTINUE
C      SF=0.00789526
C      IF(TSOT.LE.0.0.AND.TSOT.LE.5.0)SF=SF*0.048958
C      IF(TSOT.LE.5.0.AND.TSOT.LE.4.0)SF=SF*1-1117.54-0.0481/2.1*
C      C(TSOT-5.0)*TSOT1
C      IF(TSOT.LE.4.0.AND.TSOT.LE.12.0)SF=SF*1-111.048-17.541/4.
C      C(TSOT-4.0)*TSOT1
C      IF(TSOT.LE.12.0.AND.TSOT.LE.24.0)SF=SF*0.048
C
C      DO 40 J=1,3
C      DO 50 J=1,3
C      U(13,7,1)=SV1
C      H(13,7,1)=SV1
C      T(13,7,1)=TLL
C      TO(13,7,1)=TLL
C      TSOT1=TSOT
C      CONTINUE
C      TSOT=TSOT1
C      JNM1=JN-1

```

79	
30	TO113,7,41=TO112,7,41
81	TO113,7,51=TO112,7,51
82	TO113,7,51=TO112,7,51
83	CONTRACT
84	RETURN
85	END

151.000000

[illegible]

ALL INFORMATION CONTAINED
HEREIN IS UNCLASSIFIED

19	2.055,11.72,-4.44,0.0,-1,-1
20	0.0
21	1.162,9.72,-2.78,0.0,-1,-1
22	0.0
23	0.772,8.33,5.29,0.0,1,-1
24	0.0
25	0.461,7.78,5.56,0.0,1,-1
26	0.0
27	0.435,7.00,5.29,0.0,1,-1
28	0.0
29	1.186,5.28,3.89,0.0,1,-1
30	0.0


```

101-0000011.OLD7 FOR CREATED ON 5 MAY 80 AT 11:41:11
1 C.....
2 C THIS SUBROUTINE SETS THE VALUES OF THE TEMPERATURE.....
3 C.....
4 C
5 SUBROUTINE OLD7(I,J,K,IN,JN,KN,TO,TI)
6 DIMENSION T(IIN,JN,KN),T(IIN,JN,KN)
7 DO 10 I=1,IIN
8 DO 10 J=1,JN
9 DO 10 K=1,KN
10 T(I,J,K)=TO(I,J,K)
11 CONTINUE
12 RETURN
13 END

```

```

1  C.....
2  C      THIS PROGRAM SETS THE VALUES OF D AND E EQUAL TO J AND V RESPEC
3  C      IN ORDER TO RETAIN VALUES OF U AND V AT ONE TIME STEP LAG
4  C.....
5  SUBROUTINE DLOUV(I,J,K,IX,JN,KX,U,V,D,E)
6  DIMENSION UI(I,JN,KX),VI(I,JN,KX),OI(I,JN,KX),EI(I,JN,KX)
7  DO 331 K=1,KX
8  DO 331 J=1,JN
9  DO 331 I=1,IX
10     UI(I,J,K)=U(I,J,K)
11     VI(I,J,K)=V(I,J,K)
12     OI(I,J,K)=D(I,J,K)
13     EI(I,J,K)=E(I,J,K)
14     RETURN
15 END

```



```

1      *S10000000,PRITER FOR CREATED ON 14 MAY 74 AT 15:49:42
2      C.....
3      C      THIS PROGRAM PRINTS OUT THE VALUES OF NUMBER OF ITERATIONS AND
4      C      RESIDUAL ERROR IN SOLVING POISSON
5      C.....
6      SUBROUTINE PRITER(IIN,EX)
7      PRINT 5500,IIN,EX
8      FORMAT(1,' IIN= ',I4,5X,' EX= ',E15.7)
9      RETURN
10     END

```

```

1 154111, PROG SYN CREATED ON 5 MAY 80 AT 11:49:16
2 .....
3 THIS SUBROUTINE PRINTS THE VALUE OF U AND V AT ALL MAIN
4 GRID POINTS.
5 .....
6
7 SUBROUTINE PROVI1(J,A,IN,UN,AN,U,V,UA,VA,MAR)
8 DIMENSION U(1:N,1:N),V(1:N,1:N),MARI(1:N,1:N)
9 CALL IN,UN,AN,V,VA,MARI
10 DO 9100 J=1,AN
11 DO 9100 I=1,UN
12 DO 9100 L=1,N
13 U(I,I,1)=0.
14 V(I,I,1)=0.
15 IF(MARI(I,I,1).EQ.0)UA=1000000.00
16 IF(MARI(I,I,1).EQ.0)VA=1000000.00
17 CONTINUE
18 DO 150 I=1,AN
19 WRITE(6,105)I
20 DO 150 J=1,UN
21 WRITE(6,106)U(I,I,J),V(I,I,J)
22 CONTINUE
23 CONTINUE
24 DO 151 I=1,AN
25 WRITE(6,107)I
26 DO 151 J=1,UN
27 WRITE(6,108)V(I,I,J),U(I,I,J)
28 CONTINUE
29 CONTINUE
30 FORMAT(11,'U-VELOCITY FOR #2:15)
31 FORMAT(11,'V-VELOCITY FOR #2:15)
32 FORMAT(17,'2FA.2)
33 RETURN
34 END

```


1
 2
 3
 4
 5
 6
 7
 8
 9
 10
 11
 12
 13
 14
 15
 16
 17
 18
 19
 20
 21
 22
 23
 24
 25
 26
 27
 28
 29
 30
 31
 32
 33
 34
 35
 36
 37
 38
 39
 40
 41
 42
 43
 44
 45
 46
 47
 48
 49
 50
 51
 52
 53
 54
 55
 56
 57
 58
 59
 60
 61
 62
 63
 64
 65
 66
 67
 68
 69
 70
 71
 72
 73
 74
 75
 76
 77
 78
 79
 80
 81
 82
 83
 84
 85
 86
 87
 88
 89
 90
 91
 92
 93
 94
 95
 96
 97
 98
 99
 100
 101
 102
 103
 104
 105
 106
 107
 108
 109
 110
 111
 112
 113
 114
 115
 116
 117
 118
 119
 120
 121
 122
 123
 124
 125
 126
 127
 128
 129
 130
 131
 132
 133
 134
 135
 136
 137
 138
 139
 140
 141
 142
 143
 144
 145
 146
 147
 148
 149
 150
 151
 152
 153
 154
 155
 156
 157
 158
 159
 160
 161
 162
 163
 164
 165
 166
 167
 168
 169
 170
 171
 172
 173
 174
 175
 176
 177
 178
 179
 180
 181
 182
 183
 184
 185
 186
 187
 188
 189
 190
 191
 192
 193
 194
 195
 196
 197
 198
 199
 200
 201
 202
 203
 204
 205
 206
 207
 208
 209
 210
 211
 212
 213
 214
 215
 216
 217
 218
 219
 220
 221
 222
 223
 224
 225
 226
 227
 228
 229
 230
 231
 232
 233
 234
 235
 236
 237
 238
 239
 240
 241
 242
 243
 244
 245
 246
 247
 248
 249
 250
 251
 252
 253
 254
 255
 256
 257
 258
 259
 260
 261
 262
 263
 264
 265
 266
 267
 268
 269
 270
 271
 272
 273
 274
 275
 276
 277
 278
 279
 280
 281
 282
 283
 284
 285
 286
 287
 288
 289
 290
 291
 292
 293
 294
 295
 296
 297
 298
 299
 300
 301
 302
 303
 304
 305
 306
 307
 308
 309
 310
 311
 312
 313
 314
 315
 316
 317
 318
 319
 320
 321
 322
 323
 324
 325
 326
 327
 328
 329
 330
 331
 332
 333
 334
 335
 336
 337
 338
 339
 340
 341
 342
 343
 344
 345
 346
 347
 348
 349
 350
 351
 352
 353
 354
 355
 356
 357
 358
 359
 360
 361
 362
 363
 364
 365
 366
 367
 368
 369
 370
 371
 372
 373
 374
 375
 376
 377
 378
 379
 380
 381
 382
 383
 384
 385
 386
 387
 388
 389
 390
 391
 392
 393
 394
 395
 396
 397
 398
 399
 400
 401
 402
 403
 404
 405
 406
 407
 408
 409
 410
 411
 412
 413
 414
 415
 416
 417
 418
 419
 420
 421
 422
 423
 424
 425
 426
 427
 428
 429
 430
 431
 432
 433
 434
 435
 436
 437
 438
 439
 440
 441
 442
 443
 444
 445
 446
 447
 448
 449
 450
 451
 452
 453
 454
 455
 456
 457
 458
 459
 460
 461
 462
 463
 464
 465
 466
 467
 468
 469
 470
 471
 472
 473
 474
 475
 476
 477
 478
 479
 480
 481
 482
 483
 484
 485
 486
 487
 488
 489
 490
 491
 492
 493
 494
 495
 496
 497
 498
 499
 500
 501
 502
 503
 504
 505
 506
 507
 508
 509
 510
 511
 512
 513
 514
 515
 516
 517
 518
 519
 520
 521
 522
 523
 524
 525
 526
 527
 528
 529
 530
 531
 532
 533
 534
 535
 536
 537
 538
 539
 540
 541
 542
 543
 544
 545
 546
 547
 548
 549
 550
 551
 552
 553
 554
 555
 556
 557
 558
 559
 560
 561
 562
 563
 564
 565
 566
 567
 568
 569
 570
 571
 572
 573
 574
 575
 576
 577
 578
 579
 580
 581
 582
 583
 584
 585
 586
 587
 588
 589
 590
 591
 592
 593
 594
 595
 596
 597
 598
 599
 600
 601
 602
 603
 604
 605
 606
 607
 608
 609
 610
 611
 612
 613
 614
 615
 616
 617
 618
 619
 620
 621
 622
 623
 624
 625
 626
 627
 628
 629
 630
 631
 632
 633
 634
 635
 636
 637
 638
 639
 640
 641
 642
 643
 644
 645
 646
 647
 648
 649
 650
 651
 652
 653
 654
 655
 656
 657
 658
 659
 660
 661
 662
 663
 664
 665
 666
 667
 668
 669
 670
 671
 672
 673
 674
 675
 676
 677
 678
 679
 680
 681
 682
 683
 684
 685
 686
 687
 688
 689
 690
 691
 692
 693
 694
 695
 696
 697
 698
 699
 700
 701
 702
 703
 704
 705
 706
 707
 708
 709
 710
 711
 712
 713
 714
 715
 716
 717
 718
 719
 720
 721
 722
 723
 724
 725
 726
 727
 728
 729
 730
 731
 732
 733
 734
 735
 736
 737
 738
 739
 740
 741
 742
 743
 744
 745
 746
 747
 748
 749
 750
 751
 752
 753
 754
 755
 756
 757
 758
 759
 760
 761
 762
 763
 764
 765
 766
 767
 768
 769
 770
 771
 772
 773
 774
 775
 776
 777
 778
 779
 780
 781
 782
 783
 784
 785
 786
 787
 788
 789
 790
 791
 792
 793
 794
 795
 796
 797
 798
 799
 800
 801
 802
 803
 804
 805
 806
 807
 808
 809
 810
 811
 812
 813
 814
 815
 816
 817
 818
 819
 820
 821
 822
 823
 824
 825
 826
 827
 828
 829
 830
 831
 832
 833
 834
 835
 836
 837
 838
 839
 840
 841
 842
 843
 844
 845
 846
 847
 848
 849
 850
 851
 852
 853
 854
 855
 856
 857
 858
 859
 860
 861
 862
 863
 864
 865
 866
 867
 868
 869
 870
 871
 872
 873
 874
 875
 876
 877
 878
 879
 880
 881
 882
 883
 884
 885
 886
 887
 888
 889
 890
 891
 892
 893
 894
 895
 896
 897
 898
 899
 900
 901
 902
 903
 904
 905
 906
 907
 908
 909
 910
 911
 912
 913
 914
 915
 916
 917
 918
 919
 920
 921
 922
 923
 924
 925
 926
 927
 928
 929
 930
 931
 932
 933
 934
 935
 936
 937
 938
 939
 940
 941
 942
 943
 944
 945
 946
 947
 948
 949
 950
 951
 952
 953
 954
 955
 956
 957
 958
 959
 960
 961
 962
 963
 964
 965
 966
 967
 968
 969
 970
 971
 972
 973
 974
 975
 976
 977
 978
 979
 980
 981
 982
 983
 984
 985
 986
 987
 988
 989
 990
 991
 992
 993
 994
 995
 996
 997
 998
 999
 1000


```

79      DO 310 K=2,N
80      -   ASSUME=INT(I(I,J,K)*H)/H*(J+1)+1+102/21*AP*EUL-H(I(I,J),I)
81      -   IINT(I,J)=IINT(I,J)+ASSUME
82      310 CONTINUE
83      301 CONTINUE
84      301 CONTINUE
85      RETURN
86      END

```

```

.....
THIS SUBROUTINE COMPUTES YF IN THE POISSONS EQUATION
.....

```

THIS SUBROUTINE COMPUTES Ψ IN THE POISSONS EQUATION

.....

[illegible]

```

79      IF (NAT(I,J).EQ.0) GO TO 101
80      DO 110 K=2,N
81      RSUMY=(RINTY(I,J,A)+RINTY(I,J,A-1))*102/21*AP*EUL*H(I,J)
82      YINT(I,J)=YINT(I,J)+RSUMY
83      110 CONTINUE
84      101 CONTINUE
85      100 CONTINUE
86      RETURN
87      END

```



```

1 158-4154111) RWR ELT CREATED ON 5 MAY 80 AT 11:58:57
2 .....
3 THIS SUBROUTINE COMPUTES REAL VERTICAL VELOCITIES AT
4 INTEGRAL GRID POINTS.
5 .....
6 C
7 SUBROUTINE RWR(I,J,K,IN,JN,KN,U,V,W,R,HI,HT,MY,OZ,MAR)
8 DIMENSION UI(IN,JN,KN),VI(IN,JN,KN),W1(IN,JN,KN),WR(IN,JN,KN),
9 CM(IN,JN),MT(IN,JN),MY1(IN,JN),MAR1(IN,JN)
10 DO 10 I=1,IN
11 DO 10 J=1,JN
12 IF (MAR1(J).LT.11) GO TO 4
13 KKM1=KN-1
14 DO 9 K=1,KKM1
15 WR(I,J,K)=(K-1)*OZ*(UI(I,J,K)+MT(I,J)+VI(I,J,K)+MY1(I,J)+CM(I,J)
16 C=MT(I,J,K)
17 CONTINUE
18 CONTINUE
19 CONTINUE
20 RETURN
21 END

```


SA-44-111, 12-32 FOR CREATED ON 5 MAY 60 AT 12:04:20

.....
 THIS SUBROUTINE COMPUTES BOUNDARY TEMPERATURES

SUBROUTINE TEMBZII,J,K,IN,JN,KN,IO,CX,OY,OZ,MAR,CY,HI,AKI,CW,
 TAMP,HT,HTV,T,REF,TAV,TAT,TAM,GZ,OTI
 DIMENSION TII(N,JN,KN),TOI(N,JN,KN),MARII(N,JN),HXII(N,JN),HYII(N,JN)

CN=IIN,JN

HT=HTV

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT

HTV=HT


```

154-11111,UVTOP  CFI CREATD ON 19 NOV 79 AT 11:09:19
C THIS PROGRAM CALCULATES U AND V VELOCITIES AT THE SURFACE US
C BOUNDARY CONDITIONS
C-----
SUBROUTINE UVTOPIM,G,TAUT,TAUT,I,J,K,OZ,IN,JN,XN,M1,MARI
DIMENSION M1IN,JN1,MARIIN,JN1,M1IN,JN,MNI,G1IN,JN,MNI
DO 100 I=1,IN
DO 100 J=1,JN
IF MARI1,J1,LT,111 GO TO 700
111:TAUT=M111,J1
112:TAUT=M111,J1
M111,J,M111,J,M111-M111,J,M111-2*OZ*TAUT/3:
G111,J,M111,J,M111-G111,J,M111-2*OZ*TAUT/3:
CONTINUE
CONTINUE
RETURN
END
700
800

```



```

      1. WHTOP FOR CHEATED ON 14 MAY 74 AT 15150100
      2. THIS PROGRAM SETS THE VALUE OF WH EQUAL TO ZERO AT THE SURFACE
      3. SUBROUTINE WHTOP(I,J,UN,JUN,MN,MH,A,MHMI)
      4. DIMENSION WH(1:N,JUN,MN)
      5. DO 100 J=1,JUN
      6. DO 100 I=1,MN
      7. WH(I,J)=0.01 GO TO 1000
      8. CONTINUE
      9. CONTINUE
     10. RETURN
     11. END

```


LISTINGS OF PLOT PROGRAMS

Year	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100
1990	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100											

[illegible]

1
 2
 3
 4
 5
 6
 7
 8
 9
 10
 11
 12
 13
 14
 15
 16
 17
 18
 19
 20
 21
 22
 23
 24
 25
 26
 27
 28
 29
 30
 31
 32
 33
 34
 35
 36
 37
 38
 39
 40
 41
 42
 43
 44
 45
 46
 47
 48
 49
 50
 51
 52
 53
 54
 55
 56
 57
 58
 59
 60
 61
 62
 63
 64
 65
 66
 67
 68
 69
 70
 71
 72
 73
 74
 75
 76
 77
 78
 79
 80
 81
 82
 83
 84
 85
 86
 87
 88
 89
 90
 91
 92
 93
 94
 95
 96
 97
 98
 99
 100

10

1
 2
 3
 4
 5
 6
 7
 8
 9
 10
 11
 12
 13
 14
 15
 16
 17
 18
 19
 20
 21
 22
 23
 24
 25
 26
 27
 28
 29
 30
 31
 32
 33
 34
 35
 36
 37
 38
 39
 40
 41
 42
 43
 44
 45
 46
 47
 48
 49
 50
 51
 52
 53
 54
 55
 56
 57
 58
 59
 60
 61
 62
 63
 64
 65
 66
 67
 68
 69
 70
 71
 72
 73
 74
 75
 76
 77
 78
 79
 80
 81
 82
 83
 84
 85
 86
 87
 88
 89
 90
 91
 92
 93
 94
 95
 96
 97
 98
 99
 100

ORIGINAL PAGE IS
 OF POOR QUALITY

[illegible]

THE NEXT 25 LINES ARE FOR WRITING THE CAPTIONS OF THE
PLOTS. THE SPECIFIC USER MUST SCRUTINIZE THESE LINES
AND MAKE NECESSARY CHANGES.

00313 1.2100

EC. COMMON C. I. SUBROUTINE ECHRON

THIS IS ENTRY SUBROUTINE FOR AMC CONTOURING PROGRAM
(CALCOMP OR WILCO TYPE PLOTTERS)

THE COMPLETE PACKAGE CONSISTS OF 3 SUBROUTINES: ECHRON, LIMIT IN, AND END
ALL 3 ARE CATALOGUED TOGETHER IN THE UM 36C/65 UNDER MODULE NAME ECHRON
AND DECKS ARE NOT NEEDED.

ANY RECTANGULAR GRIDDED SCALAR FIELD CAN BE CONTOURED ON WILCO
OR CALCOMP TYPE PLOTTER BY SETTING UP PROPER CALLING ARGUMENTS AND
PROCEDURES AS INDICATED BELOW AND THEN CALLING ECHRON.

-----CALLING STATEMENT IS AS FOLLOWS-----

CALL ECHRON(MH, IN1, IN2, NE1, NE2, NE11, NE12, H1, W1, PLTINC, SAMCON,
CONTINT, PGRID, IN3, IN4, ZLIT, ZBIG, ANGRTH, ASOUTH, ACST, ACST, NCASHO,
NCASHU, XLABEL, SHOOTM, TRECCT)

---DESCRIPTION OF CALLING ARGUMENTS---

MH IS ARRAY CONTAINING GRID DATA TO BE CONTOURED. ITS DIMENSIONS
ARE IN1 AND IN2. DIMENSION MH(IN1, IN2). POINT 1,1 IS LOWER LEFT
CORNER OF GRID. IN1 IS DIMENSION IN X DIRECTION AND IN2 IS
DIMENSION IN Y DIRECTION.
(X INCREASES FROM WEST TO EAST AND Y INCREASES FROM SOUTH TO NORTH)

NE1, NE2, NE11, AND NE12 DETERMINE THE PORTION OF MH GRID TO
BE USED. NE1 AND NE2 ARE THE FIRST(LEFTMOST) AND LAST(RIGHTMOST)
COLUMNS TO BE USED. NE11 AND NE12 ARE THE FIRST(BOTTOM) AND LAST(TOP)
ROWS TO BE USED. (THUS ANY SECTION OF MH CAN BE USED)
FOR FULL GRID----

NE1 > 1
NE2 > IN1
NE11 > 1
NE12 > IN2

H1 IS HEIGHT IN INCHES OF CONTOUR MAP BETWEEN LIMITS NE11 AND NE12
W1 IS WIDTH IN INCHES OF CONTOUR MAP BETWEEN LIMITS NE1 AND NE2

PLTINC IS STRAIGHT LINE PLOT INCREMENT IN INCHES TO BE USED
ALONG CONTOUR. GOOD VALUE IS .04, BUT CAN BE VARIED UP OR DOWN.
SINCE LARGER VALUES CAUSE PROGRAM TO RUN A LITTLE FASTER, TOTAL VALUE
IS LARGEST THAT WILL STILL GIVE SMOOTH LOOKING CURVES.
DO SOME EXPERIMENTING WITH IT. START WITH .03 OR .04 AND INCREASE.

SAMCON IS ANY SAMPLE CONTOUR VALUE. IT IS USED AS A STARTING POINT
FOR COUNTING UP AND DOWN TO GET OTHER CONTOUR VALUES.

CONTINT IS CONTOUR INTERVAL TO BE USED.

PGRID IS AN INTEGER*2 STORAGE ARRAY USED INTERNALLY IN PROGRAM
AND NEED NOT BE INITIALIZED. IT IS INCLUDED AS ARGUMENT IN ORDER
TO TAKE ADVANTAGE OF VARIABLE DIMENSIONS. DECLARE AS INTEGER*2
BEFORE CALLING.

IN3 AND IN4 ARE X AND Y DIMENSIONS OF PGRID. DIMENSION PGRID(IN3, IN4)
IN3 MUST BE AT LEAST AS LARGE AS NE2-NE1+1
IN4 MUST BE AT LEAST AS LARGE AS NE12-NE11+1
(THUS PGRID MUST BE AS LARGE AS PORTION OF DATA ARRAY MH BEING USED)

ZLIT AND ZBIG ARE LOWER AND UPPER CONTOUR CHECK LIMITS. (Z CONTOUR
WILL BE DRAWN ONLY IF VALUE OF ZLIT OR ABOVE VALUE OF ZBIG)
(USEFUL TO PREVENT DRAWING FOR ANY COMPLETELY WILD DATA)

ANGRTH, ASOUTH, ACST, AND ACST CAN BE USED TO ELIMINATE ANY
NUMBER OF INCHES FROM ANY SIDE OF FINAL DRAWING.

FOR FULL DRAWING WITH HEIGHT H1 AND WIDTH W1.
INITIALIZE ALL 4 OF ABOVE ARGUMENTS TO ZERO.

FOR EACH OF THE ABOVE WITH POSITIVE VALUE, THIS MANY INCHES
WILL BE ELIMINATED ON SIDE TO WHICH IT APPLIES.
THIS ALLOWS US TO FIT ANY RECTANGULAR GRID TO ANY RECTANGLE
OR OTHER MAP LIMITS WITHOUT ACTUALLY ADJUSTING THE GRID.

NCASHO AND NCASHU CONTROL TYPE OF CONTOURS (ESCLD IN DASHED LINES)

ORIGINAL PAGE IS
OF POOR QUALITY

```

SUBROUTINE CCHADIMH, IN1, IN2, NEX1, NEX2, NEX3, NEX4, N1, N10, PLTINC,
  SAMPON, COVINT, ZGRID, IY1, IY2, LIT, ZBIG, ANORTH, ASOUTH, ACST, AUCS1,
  IOASHD, IOASHM, LABEL, SMOOTH, IRECVI

```

```

CJMHQS /STRCON/SMH1,SMH1,1,Y,IGRID,YGRID,CUTOF,SMH1,SO=1,IMA1,APP.
CVP,CJIG,U,V,NHUS,JOJO,NHUV,NHUV,TJTH,SOUTH,LIST,=CST,CLIT,CBIG.
CCL1,CCL1,C435,INC,CLOST,PVAL,PVOL,NENTER,NHUM,NH1,NH1,
C441,C441,NH1,NOSINC,VALLIN,MINC,MAICRO,=HAT,LOASH1,LOASH2,DASHER,
SOOL1,CJUL
CJMHQS /GENDEQ/HJLN,JOJO,MOGH,XLAST,YLAST
LOGICAL DASHER,DOLABS,QUI
DIMENSION MH1(1,1,2),MH1(1,1,1),MH1(1,1)
CJMHQS /GRID
CJMHQS /MAP/0/

```

UNIQUE MAP: 12 14 20 MINCOMING AGOURNIZ FOLLOWER
12 14 20 MINCOMING AGOURNIZ FOLLOWER
12 14 20 MINCOMING AGOURNIZ FOLLOWER
12 14 20 MINCOMING AGOURNIZ FOLLOWER

התאחדות המורים

THERE ARE 2 SCANS FOR EACH CONTOUR VALUE. FIRST WITH VARIABLE OUIS AS FALSE SELECTS ONLY CONTOURS ENTERING GRID FROM OUTSIDE EDGES. SECOND SCAN WITH OUIS TRUE SELECTS REMAINING INNER CONTOURS. STARTING POINT CLOSEST TO PLOT PEN POSITION IS SELECTED IN EACH CASE.

1. **Introduction**
 2. **Background**
 3. **Methodology**
 4. **Results**
 5. **Discussion**
 6. **Conclusion**
 7. **References**
 8. **Appendix**
 9. **Tables**
 10. **Figures**
 11. **Supplementary Materials**
 12. **Author Contributions**
 13. **Funding**
 14. **Conflicts of Interest**
 15. **Acknowledgments**
 16. **References**
 17. **Appendix**
 18. **Tables**
 19. **Figures**
 20. **Supplementary Materials**
 21. **Author Contributions**
 22. **Funding**
 23. **Conflicts of Interest**
 24. **Acknowledgments**
 25. **References**
 26. **Appendix**
 27. **Tables**
 28. **Figures**
 29. **Supplementary Materials**
 30. **Author Contributions**
 31. **Funding**
 32. **Conflicts of Interest**
 33. **Acknowledgments**
 34. **References**
 35. **Appendix**
 36. **Tables**
 37. **Figures**
 38. **Supplementary Materials**
 39. **Author Contributions**
 40. **Funding**
 41. **Conflicts of Interest**
 42. **Acknowledgments**
 43. **References**
 44. **Appendix**
 45. **Tables**
 46. **Figures**
 47. **Supplementary Materials**
 48. **Author Contributions**
 49. **Funding**
 50. **Conflicts of Interest**
 51. **Acknowledgments**
 52. **References**
 53. **Appendix**
 54. **Tables**
 55. **Figures**
 56. **Supplementary Materials**
 57. **Author Contributions**
 58. **Funding**
 59. **Conflicts of Interest**
 60. **Acknowledgments**
 61. **References**
 62. **Appendix**
 63. **Tables**
 64. **Figures**
 65. **Supplementary Materials**
 66. **Author Contributions**
 67. **Funding**
 68. **Conflicts of Interest**
 69. **Acknowledgments**
 70. **References**
 71. **Appendix**
 72. **Tables**
 73. **Figures**
 74. **Supplementary Materials**
 75. **Author Contributions**
 76. **Funding**
 77. **Conflicts of Interest**
 78. **Acknowledgments**
 79. **References**
 80. **Appendix**
 81. **Tables**
 82. **Figures**
 83. **Supplementary Materials**
 84. **Author Contributions**
 85. **Funding**
 86. **Conflicts of Interest**
 87. **Acknowledgments**
 88. **References**
 89. **Appendix**
 90. **Tables**
 91. **Figures**
 92. **Supplementary Materials**
 93. **Author Contributions**
 94. **Funding**
 95. **Conflicts of Interest**
 96. **Acknowledgments**
 97. **References**
 98. **Appendix**
 99. **Tables**
 100. **Figures**
 101. **Supplementary Materials**
 102. **Author Contributions**
 103. **Funding**
 104. **Conflicts of Interest**
 105. **Acknowledgments**
 106. **References**
 107. **Appendix**
 108. **Tables**
 109. **Figures**
 110. **Supplementary Materials**
 111. **Author Contributions**
 112. **Funding**
 113. **Conflicts of Interest**
 114. **Acknowledgments**
 115. **References**
 116. **Appendix**
 117. **Tables**
 118. **Figures**
 119. **Supplementary Materials**
 120. **Author Contributions**
 121. **Funding**
 122. **Conflicts of Interest**
 123. **Acknowledgments**
 124. **References**
 125. **Appendix**
 126. **Tables**
 127. **Figures**
 128. **Supplementary Materials**
 129. **Author Contributions**
 130. **Funding**
 131. **Conflicts of Interest**
 132. **Acknowledgments**
 133. **References**
 134. **Appendix**
 135. **Tables**
 136. **Figures**
 137. **Supplementary Materials**
 138. **Author Contributions**
 139. **Funding**
 140. **Conflicts of Interest**
 141. **Acknowledgments**
 142. **References**
 143. **Appendix**
 144. **Tables**
 145. **Figures**
 146. **Supplementary Materials**
 147. **Author Contributions**
 148. **Funding**
 149. **Conflicts of Interest**
 150. **Acknowledgments**
 151. **References**
 152. **Appendix**
 153. **Tables**
 154. **Figures**
 155. **Supplementary Materials**
 156. **Author Contributions**
 157. **Funding**
 158. **Conflicts of Interest**
 159. **Acknowledgments**
 160. **References**
 161. **Appendix**
 162. **Tables**
 163. **Figures**
 164. **Supplementary Materials**
 165. **Author Contributions**
 166. **Funding**
 167. **Conflicts of Interest**
 168. **Acknowledgments**
 169. **References**
 170. **Appendix**
 171. **Tables**
 172. **Figures**
 173. **Supplementary Materials**
 174. **Author Contributions**
 175. **Funding**
 176. **Conflicts of Interest**
 177. **Acknowledgments**
 178. **References**
 179. **Appendix**
 180. **Tables**
 181. **Figures**
 182. **Supplementary Materials**
 183. **Author Contributions**
 184. **Funding**
 185. **Conflicts of Interest**
 186. **Acknowledgments**
 187. **References**
 188. **Appendix**
 189. **Tables**
 190. **Figures**
 191. **Supplementary Materials**
 192. **Author Contributions**
 193. **Funding**
 194. **Conflicts of Interest**
 195. **Acknowledgments**
 196. **References**
 197. **Appendix**
 198. **Tables**
 199. **Figures**
 200. **Supplementary Materials**
 201. **Author Contributions**
 202. **Funding**
 203. **Conflicts of Interest**
 204. **Acknowledgments**
 205. **References**
 206. **Appendix**
 207. **Tables**
 208. **Figures**
 209. **Supplementary Materials**
 210. **Author Contributions**
 211. **Funding**
 212. **Conflicts of Interest**
 213. **Acknowledgments**
 214. **References**
 215. **Appendix**
 216. **Tables**
 217. **Figures**
 218. **Supplementary Materials**
 219. **Author Contributions**
 220. **Funding**
 221. **Conflicts of Interest**
 222. **Acknowledgments**
 223. **References**
 224. **Appendix**
 225. **Tables**
 226. **Figures**
 227. **Supplementary Materials**
 228. **Author Contributions**
 229. **Funding**
 230. **Conflicts of Interest**
 231. **Acknowledgments**
 232. **References**
 233. **Appendix**
 234. **Tables**
 235. **Figures**
 236. **Supplementary Materials**
 237. **Author Contributions**
 238. **Funding**
 239. **Conflicts of Interest**
 240. **Acknowledgments**
 241. **References**
 242. **Appendix**
 243. **Tables**
 244. **Figures**
 245. **Supplementary Materials**
 246. **Author Contributions**

111

```

      IF (PVAL .EQ. 0) THEN
        GO TO 100
      ELSE
        GO TO 110
      END IF
    CONTINUE
    IF (PVAL .GT. 0) THEN
      IF (PVAL .GT. 99999) THEN
        PVAL = 99999
      ELSE
        PVAL = PVAL
      END IF
    ELSE
      IF (PVAL .LT. -99999) THEN
        PVAL = -99999
      ELSE
        PVAL = PVAL
      END IF
    END IF
    WRITE(16,13) PVAL, DOLABS, OUTS
121 FOR=41111, 213.5, 213.5
    NEXT CALL SUBROUTINE CONLIN TO ACTUALLY DRAW CONTOUR WITH VALUE PV
    CALL CONLIN(INH, IN1, IN2, RGRID, IN3, IN4)
    NOW GO BACK TO INNER LOOP TO SEE IF THERE ARE OTHER PVAL CONTOURS
    TO BE DRAWN.
122 GO TO 18
    IF (PVAL .EQ. 0) GO TO 612
    OUTS = OUTS + 1
    GO TO 13
123 PVAL = PVAL + CONINC
    INCREMENT CONTOUR AND GO TO TOP OF LOOP FOR NEXT CONTOUR
    GO TO 18
110 CALL PLOTIC(0, 0, -3)
    INAP = INAP + 1
    INECCT = INECCT + 1
    WRITE(16,111) INAP, INECCT, INECCT
111 FOR=1, 1, 1
    INCONTOUR = INAP, 13, 24M BEGINS WITH PLOT RECORD, 13, 14M
    WRITE(16,112) INCONTOUR, VALLIN, MACRO, MAC1
112 FORMAT(12X, 21HMOST LINE INCREMENTS, 13, 12H ON CONTOUR, F10.2, /, 12X
    2 12HMOST SQUARES, 14, 12H ON CONTOUR, F10.2, /)
120 RETURN
    END

```



```

      CONTINUE 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100, 101, 102, 103, 104, 105, 106, 107, 108, 109, 110, 111, 112, 113, 114, 115, 116, 117, 118, 119, 120, 121, 122, 123, 124, 125, 126, 127, 128, 129, 130, 131, 132, 133, 134, 135, 136, 137, 138, 139, 140, 141, 142, 143, 144, 145, 146, 147, 148, 149, 150, 151, 152, 153, 154, 155, 156, 157, 158, 159, 160, 161, 162, 163, 164, 165, 166, 167, 168, 169, 170, 171, 172, 173, 174, 175, 176, 177, 178, 179, 180, 181, 182, 183, 184, 185, 186, 187, 188, 189, 190, 191, 192, 193, 194, 195, 196, 197, 198, 199, 200, 201, 202, 203, 204, 205, 206, 207, 208, 209, 210, 211, 212, 213, 214, 215, 216, 217, 218, 219, 220, 221, 222, 223, 224, 225, 226, 227, 228, 229, 230, 231, 232, 233, 234, 235, 236, 237, 238, 239, 240, 241, 242, 243, 244, 245, 246, 247, 248, 249, 250, 251, 252, 253, 254, 255, 256, 257, 258, 259, 260, 261, 262, 263, 264, 265, 266, 267, 268, 269, 270, 271, 272, 273, 274, 275, 276, 277, 278, 279, 280, 281, 282, 283, 284, 285, 286, 287, 288, 289, 290, 291, 292, 293, 294, 295, 296, 297, 298, 299, 300, 301, 302, 303, 304, 305, 306, 307, 308, 309, 310, 311, 312, 313, 314, 315, 316, 317, 318, 319, 320, 321, 322, 323, 324, 325, 326, 327, 328, 329, 330, 331, 332, 333, 334, 335, 336, 337, 338, 339, 340, 341, 342, 343, 344, 345, 346, 347, 348, 349, 350, 351, 352, 353, 354, 355, 356, 357, 358, 359, 360, 361, 362, 363, 364, 365, 366, 367, 368, 369, 370, 371, 372, 373, 374, 375, 376, 377, 378, 379, 380, 381, 382, 383, 384, 385, 386, 387, 388, 389, 390, 391, 392, 393, 394, 395, 396, 397, 398, 399, 400, 401, 402, 403, 404, 405, 406, 407, 408, 409, 410, 411, 412, 413, 414, 415, 416, 417, 418, 419, 420, 421, 422, 423, 424, 425, 426, 427, 428, 429, 430, 431, 432, 433, 434, 435, 436, 437, 438, 439, 440, 441, 442, 443, 444, 445, 446, 447, 448, 449, 450, 451, 452, 453, 454, 455, 456, 457, 458, 459, 460, 461, 462, 463, 464, 465, 466, 467, 468, 469, 470, 471, 472, 473, 474, 475, 476, 477, 478, 479, 480, 481, 482, 483, 484, 485, 486, 487, 488, 489, 490, 491, 492, 493, 494, 495, 496, 497, 498, 499, 500, 501, 502, 503, 504, 505, 506, 507, 508, 509, 510, 511, 512, 513, 514, 515, 516, 517, 518, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 532, 533, 534, 535, 536, 537, 538, 539, 540, 541, 542, 543, 544, 545, 546, 547, 548, 549, 550, 551, 552, 553, 554, 555, 556, 557, 558, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 571, 572, 573, 574, 575, 576, 577, 578, 579, 580, 581, 582, 583, 584, 585, 586, 587, 588, 589, 590, 591, 592, 593, 594, 595, 596, 597, 598, 599, 600, 601, 602, 603, 604, 605, 606, 607, 608, 609, 610, 611, 612, 613, 614, 615, 616, 617, 618, 619, 620, 621, 622, 623, 624, 625, 626, 627, 628, 629, 630, 631, 632, 633, 634, 635, 636, 637, 638, 639, 640, 641, 642, 643, 644, 645, 646, 647, 648, 649, 650, 651, 652, 653, 654, 655, 656, 657, 658, 659, 660, 661, 662, 663, 664, 665, 666, 667, 668, 669, 670, 671, 672, 673, 674, 675, 676, 677, 678, 679, 680, 681, 682, 683, 684, 685, 686, 687, 688, 689, 690, 691, 692, 693, 694, 695, 696, 697, 698, 699, 700, 701, 702, 703, 704, 705, 706, 707, 708, 709, 710, 711, 712, 713, 714, 715, 716, 717, 718, 719, 720, 721, 722, 723, 724, 725, 726, 727, 728, 729, 730, 731, 732, 733, 734, 735, 736, 737, 738, 739, 740, 741, 742, 743, 744, 745, 746, 747, 748, 749, 750, 751, 752, 753, 754, 755, 756, 757, 758, 759, 760, 761, 762, 763, 764, 765, 766, 767, 768, 769, 770, 771, 772, 773, 774, 775, 776, 777, 778, 779, 780, 781, 782, 783, 784, 785, 786, 787, 788, 789, 790, 791, 792, 793, 794, 795, 796, 797, 798, 799, 800, 801, 802, 803, 804, 805, 806, 807, 808, 809, 810, 811, 812, 813, 814, 815, 816, 817, 818, 819, 820, 821, 822, 823, 824, 825, 826, 827, 828, 829, 830, 831, 832, 833, 834, 835, 836, 837, 838, 839, 840, 841, 842, 843, 844, 845, 846
```

SAMPLE RUN

[illegible]

U-VELOCITY FOR A:

.30	.30	.30	.00	.00	.00	.00	-1.39	-1.39	-1.39	-1.39	-1.39	-1.39	-1.39	-1.39	-1.39	-1.39	-1.39	-1.39	.00
.30	.30	.30	.00	.00	.00	.00	-.91	-.89	-.83	-.74	-.70	-.67	-.64	-.62	-.55	-.25	-.00	-.29	.33
.30	.30	.30	.00	.00	.00	.00	-.40	-.93	-.85	-.72	-.73	-.70	-.71	-.75	-.71	.09	.00	.00	.00
.30	.30	.30	.00	.00	.00	.00	-.25	-.74	-.88	-.94	-.77	-.73	-.71	-.73	-.77	-.67	.03	.03	.30
.30	.30	.30	.00	.00	.00	.00	-.45	-.73	-.81	-.74	-.74	-.70	-.65	-.70	-.72	-.54	.03	.00	.00
.00	.00	.00	.00	.00	.00	.00	-.66	-.80	-.79	-.73	-.67	-.64	-.62	-.60	-.62	-.63	.03	.00	.00
.30	.30	.30	.00	-.62	.00	-.83	-.95	-.75	-.67	-.62	-.56	-.54	-.47	-.36	-.29	.02	.22	.12	.00
.30	.30	.30	-.55	-.94	-.81	-.84	-.75	-.66	-.59	-.55	-.52	-.48	-.38	-.31	.03	.03	-.06	.03	.00
.30	.30	.30	-1.42	-1.34	-.93	-.71	-.58	-.52	-.46	-.45	-.43	-.42	-.33	.00	.00	.00	-.07	.03	.00
.30	.30	.30	-2.44	-1.61	-.74	-.42	-.35	-.36	-.37	-.34	-.31	-.31	-.31	.00	.00	.00	.00	.00	.00
.30	-1.35	-.40	-2.00	-.93	-.26	-.06	-.22	-.23	-.26	-.21	-.16	-.20	-.32	.00	.00	.00	.00	.00	.00
.30	.30	.30	.00	.00	.00	.00	.33	-.39	-.12	.00	.00	.00	-.24	.02	.07	.03	.00	.00	.00
.30	.30	.30	.00	.00	.00	.00	.30	-.04	-.04	.00	.00	.00	-.12	-.07	.05	.03	.00	.00	.00
.30	.30	.30	.00	.00	.00	.00	.09	-.01	.03	.00	.00	.00	.00	-.05	-.00	.00	.00	.00	.00
.30	.30	.30	.00	.00	.00	.00	.00	-.10	.03	.00	.00	.00	.00	.00	-.05	-.01	-.02	.00	.00
.30	.30	.30	.00	.00	.00	.00	.33	-.37	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
.30	.30	.30	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00

0.32	0.33	0.30	0.32	0.30	0.37	0.31	-1.39	-1.73	-1.39	-1.79	-1.74	-1.35	-1.35	-1.29	-1.35	-1.39	-1.35	-1.39	0.33
0.30	0.30	0.30	0.30	0.30	0.30	0.31	-0.96	-0.95	-0.97	-0.81	-0.78	-0.74	-0.71	-0.69	-0.62	-0.31	-0.13	-0.33	0.00
0.32	0.33	0.30	0.30	0.00	0.30	0.00	-0.94	-0.90	-0.90	-0.83	-0.78	-0.76	-0.77	-0.81	-0.75	0.33	0.00	0.30	0.00
0.30	0.30	0.30	0.30	0.00	-0.32	-0.29	-0.75	-0.92	-0.48	-0.61	-0.76	-0.77	-0.79	-0.82	-0.79	0.33	0.00	0.00	0.00
0.33	0.30	0.30	0.30	0.30	0.32	-0.50	-0.73	-0.95	-0.84	-0.75	-0.75	-0.74	-0.75	-0.77	-0.62	0.33	0.03	0.33	0.33
0.00	0.00	0.30	0.30	0.00	0.30	-0.71	-0.85	-0.84	-0.79	-0.74	-0.70	-0.66	-0.66	-0.67	-0.64	0.33	0.30	0.30	0.00
0.00	0.33	0.30	0.00	-0.64	0.00	-0.97	-0.91	-0.81	-0.73	-0.69	-0.64	-0.60	-0.54	-0.42	-0.34	-0.24	0.16	0.07	0.00
0.32	0.30	0.30	-0.57	-0.94	-0.63	-0.89	-0.92	-0.72	-0.65	-0.61	-0.52	-0.55	-0.44	-0.13	0.00	0.33	-0.11	0.33	0.00
0.30	0.30	0.30	-1.70	-1.37	-0.97	-0.75	-0.54	-0.59	-0.55	-0.50	-0.50	-0.48	-0.39	0.00	0.33	0.33	-0.11	0.30	0.30
0.00	0.33	0.30	-1.73	-1.61	-0.70	-0.40	-0.40	-0.43	-0.44	-0.41	-0.38	-0.39	-0.36	0.00	0.00	0.33	0.00	0.00	0.00
0.30	-1.50	-0.74	-1.44	-0.87	-0.40	-0.14	-0.19	-0.28	-0.32	-0.27	-0.20	-0.24	-0.33	0.00	0.00	0.33	0.00	0.00	0.00
0.30	0.30	0.30	0.30	0.30	0.30	0.01	-0.30	-0.15	-0.13	0.00	0.00	0.00	-0.33	-0.34	0.01	0.00	0.00	0.30	0.00
0.33	0.33	0.30	0.30	0.00	0.30	0.00	0.30	-0.39	-0.34	0.00	0.00	0.00	-0.14	-0.10	-0.02	-0.33	0.33	0.33	0.33
0.30	0.30	0.30	0.30	0.30	0.30	0.00	0.30	-0.00	0.00	0.00	0.00	0.00	0.00	-0.11	-0.06	0.00	0.00	0.00	0.00
0.00	0.30	0.30	0.30	0.30	0.00	0.30	0.30	-0.10	0.00	0.00	0.00	0.00	0.00	-0.10	-0.07	-0.07	0.00	0.00	0.00
0.30	0.30	0.30	0.30	0.30	0.30	0.30	0.30	-0.11	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.30	0.00	0.00	0.00
0.30	0.30	0.30	0.30	0.30	0.30	0.00	0.30	0.30	0.30	0.30	0.00	0.30	0.30	0.30	0.00	0.30	0.30	0.30	0.30

U-VELOCITY F24 4

.00	.00	.00	.00	.00	.00	.00	-1.39	-1.39	-1.39	-1.39	-1.39	-1.39	-1.39	-1.39	-1.39	-1.39	-1.39	-1.39	.00
.00	.00	.00	.00	.00	.00	.00	-.75	-.75	-.69	-.65	-.63	-.60	-.58	-.57	-.57	-.27	-.12	-.29	.00
.00	.00	.00	.00	.00	.00	.00	-.66	-.76	-.72	-.64	-.61	-.60	-.61	-.65	-.62	.00	.00	.00	.00
.00	.00	.00	.00	.00	.00	.00	-.23	-.61	-.72	-.64	-.61	-.60	-.62	-.65	-.57	.00	.00	.00	.00
.00	.00	.00	.00	.00	.00	.00	-.35	-.61	-.67	-.66	-.62	-.59	-.56	-.59	-.51	-.45	.00	.00	.00
.00	.00	.00	.00	.00	.00	.00	-.56	-.64	-.65	-.62	-.55	-.55	-.53	-.52	-.52	-.57	.00	.00	.00
.00	.00	.00	.00	-.44	.00	-.73	-.72	-.64	-.59	-.54	-.51	-.48	-.43	-.33	-.26	-.03	.13	.05	.00
.00	.00	.00	-.41	-.75	-.65	-.71	-.65	-.57	-.52	-.41	-.40	-.44	-.36	-.30	.00	.00	-.11	.00	.00
.00	.00	.00	-.55	-1.01	-.75	-.54	-.51	-.46	-.44	-.41	-.35	-.39	-.31	.00	.00	.00	-.10	.00	.00
.00	.00	.00	-2.17	-1.24	-.59	-.37	-.32	-.34	-.35	-.32	-.32	-.31	-.26	.00	.00	.00	.00	.00	.00
.00	-1.32	-1.71	-1.35	-.62	-.21	-.11	-.15	-.22	-.22	-.21	-.17	-.21	-.13	.00	.00	.00	.00	.00	.00
.00	.00	.75	.00	.00	.00	-.01	-.75	-.12	-.15	.70	.00	.00	-.25	-.34	.01	.00	.00	.00	.00
.00	.00	.00	.00	.00	.00	.00	.00	-.02	-.07	.00	.00	.00	-.15	-.29	-.02	.00	.00	.00	.00
.00	.00	.00	.00	.00	.00	.00	.00	-.01	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
.00	.00	.00	.00	.00	.00	.00	.00	-.17	.00	.70	.70	.00	.00	-.79	-.77	-.36	.00	.00	.00
.00	.00	.00	.00	.00	.00	.00	.00	-.09	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00

[illegible]

127

	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9
.00	.00	.01	.02	.03	.04	.05	.06	.07	.08	.09	.10	.11	.12	.13	.14	.15	.16	.17	.18	.19
.20	.20	.21	.22	.23	.24	.25	.26	.27	.28	.29	.30	.31	.32	.33	.34	.35	.36	.37	.38	.39
.40	.40	.41	.42	.43	.44	.45	.46	.47	.48	.49	.50	.51	.52	.53	.54	.55	.56	.57	.58	.59
.60	.60	.61	.62	.63	.64	.65	.66	.67	.68	.69	.70	.71	.72	.73	.74	.75	.76	.77	.78	.79
.80	.80	.81	.82	.83	.84	.85	.86	.87	.88	.89	.90	.91	.92	.93	.94	.95	.96	.97	.98	.99
.00	.00	.01	.02	.03	.04	.05	.06	.07	.08	.09	.10	.11	.12	.13	.14	.15	.16	.17	.18	.19
.20	.20	.21	.22	.23	.24	.25	.26	.27	.28	.29	.30	.31	.32	.33	.34	.35	.36	.37	.38	.39
.40	.40	.41	.42	.43	.44	.45	.46	.47	.48	.49	.50	.51	.52	.53	.54	.55	.56	.57	.58	.59
.60	.60	.61	.62	.63	.64	.65	.66	.67	.68	.69	.70	.71	.72	.73	.74	.75	.76	.77	.78	.79
.80	.80	.81	.82	.83	.84	.85	.86	.87	.88	.89	.90	.91	.92	.93	.94	.95	.96	.97	.98	.99
.00	.00	.01	.02	.03	.04	.05	.06	.07	.08	.09	.10	.11	.12	.13	.14	.15	.16	.17	.18	.19
.20	.20	.21	.22	.23	.24	.25	.26	.27	.28	.29	.30	.31	.32	.33	.34	.35	.36	.37	.38	.39
.40	.40	.41	.42	.43	.44	.45	.46	.47	.48	.49	.50	.51	.52	.53	.54	.55	.56	.57	.58	.59
.60	.60	.61	.62	.63	.64	.65	.66	.67	.68	.69	.70	.71	.72	.73	.74	.75	.76	.77	.78	.79
.80	.80	.81	.82	.83	.84	.85	.86	.87	.88	.89	.90	.91	.92	.93	.94	.95	.96	.97	.98	.99
.00	.00	.01	.02	.03	.04	.05	.06	.07	.08	.09	.10	.11	.12	.13	.14	.15	.16	.17	.18	.19
.20	.20	.21	.22	.23	.24	.25	.26	.27	.28	.29	.30	.31	.32	.33	.34	.35	.36	.37	.38	.39
.40	.40	.41	.42	.43	.44	.45	.46	.47	.48	.49	.50	.51	.52	.53	.54	.55	.56	.57	.58	.59
.60	.60	.61	.62	.63	.64	.65	.66	.67	.68	.69	.70	.71	.72	.73	.74	.75	.76	.77	.78	.79
.80	.80	.81	.82	.83	.84	.85	.86	.87	.88	.89	.90	.91	.92	.93	.94	.95	.96	.97	.98	.99
.00	.00	.01	.02	.03	.04	.05	.06	.07	.08	.09	.10	.11	.12	.13	.14	.15	.16	.17	.18	.19
.20	.20	.21	.22	.23	.24	.25	.26	.27	.28	.29	.30	.31	.32	.33	.34	.35	.36	.37	.38	.39
.40	.40	.41	.42	.43	.44	.45	.46	.47	.48	.49	.50	.51	.52	.53	.54	.55	.56	.57	.58	.59
.60	.60	.61	.62	.63	.64	.65	.66	.67	.68	.69	.70	.71	.72	.73	.74	.75	.76	.77	.78	.79
.80	.80	.81	.82	.83	.84	.85	.86	.87	.88	.89	.90	.91	.92	.93	.94	.95	.96	.97	.98	.99
.00	.00	.01	.02	.03	.04	.05	.06	.07	.08	.09	.10	.11	.12	.13	.14	.15	.16	.17	.18	.19

V-VELOCITY FOR 43

.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
.10	.00	.00	.00	.00	.00	.00	-.04	-.03	.04	.07	.11	.13	.14	.30	.50	.73	.75	.87	.00
.20	.00	.00	.00	.00	.00	.00	.22	.17	.17	.17	.18	.20	.24	.33	.36	.33	.00	.00	.00
.30	.00	.00	.00	.00	.00	.00	.45	.43	.34	.28	.24	.22	.21	.20	.20	.18	.33	.00	.00
.40	.00	.00	.00	.00	.00	.00	.31	.41	.40	.35	.30	.25	.21	.15	.10	.07	.33	.00	.00
.50	.00	.00	.00	.00	.00	.00	.31	.42	.44	.40	.35	.26	.22	.12	-.02	-.14	.00	.00	.00
.60	.00	.00	.00	.00	.00	.00	.52	.57	.53	.46	.39	.32	.25	.15	-.06	-.43	-.62	-.22	.16
.70	.00	.00	.00	.00	.00	.00	.76	.67	.52	.43	.35	.26	.24	.14	.03	.33	.01	.33	.33
.80	.00	.00	.00	.00	1.13	1.25	1.10	.86	.70	.56	.46	.35	.27	.22	.33	.00	.33	.14	.33
.90	.00	.00	.00	1.27	1.04	1.04	1.22	.92	.71	.57	.47	.33	.21	.16	.30	.00	.00	.00	.00
1.00	1.27	1.04	1.04	1.25	1.12	1.04	.91	.62	.50	.35	.25	.08	.01	.33	.00	.33	.33	.33	.00
1.10	.00	.00	.00	.00	.00	.00	.52	.43	.30	.20	.00	.00	-.01	-.09	.16	.33	.00	.33	.33
1.20	.00	.00	.00	.00	.00	.00	.00	.10	.17	.20	.00	.00	.14	.00	.12	.00	.00	.00	.00
1.30	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.15	.16	.00	.00	.30	.00
1.40	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.18	.20	.24	.00	.00
1.50	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
1.60	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00

V-VELOCITY FOR 42

.35	.35	.36	.35	.35	.35	.35	.33	.33	.33	.36	.35	.35	.35	.33	.33	.33	.33	.33	.33
.35	.35	.36	.35	.35	.35	.35	.32	.23	.31	.36	.36	.40	.45	.51	.76	.95	1.01	1.04	.00
.35	.35	.36	.35	.35	.35	.35	.47	.47	.48	.49	.50	.51	.55	.60	.61	.60	.30	.30	.00
.35	.35	.36	.35	.35	.35	.35	.72	.65	.59	.56	.54	.53	.52	.51	.43	.33	.30	.30	.00
.35	.35	.36	.35	.35	.35	.35	.54	.73	.73	.66	.51	.57	.53	.48	.41	.33	.30	.30	.00
.35	.35	.36	.35	.35	.35	.35	.55	.72	.75	.71	.66	.61	.54	.45	.35	.13	.30	.30	.00
.35	.35	.36	.35	.35	.35	.35	.76	.86	.83	.77	.70	.64	.57	.47	.25	-.16	-.42	-.51	.31
.35	.35	.36	.35	.35	.35	.35	1.09	1.17	1.15	.97	.97	.74	.66	.60	.54	.41	.30	.30	.30
.35	.35	.36	.35	.35	.35	.35	1.32	1.51	1.12	1.14	1.00	.87	.77	.67	.58	.47	.30	.30	.30
.35	.35	.36	.35	.35	.35	.35	1.69	2.25	1.44	1.45	1.21	1.01	.87	.77	.63	.50	.40	.30	.30
6.84	3.67	3.47	2.91	2.22	1.62	1.33	1.09	.97	.79	.64	.51	.33	.26	.30	.30	.30	.30	.30	.30
.35	.35	.36	.35	.35	.35	.35	.64	.75	.77	.55	.30	.30	.30	.23	.15	.35	.30	.30	.30
.35	.35	.36	.35	.35	.35	.35	.30	.41	.36	.30	.30	.30	.34	.35	.36	.30	.30	.30	.30
.35	.35	.36	.35	.35	.35	.35	.30	.28	.33	.30	.30	.30	.30	.30	.30	.30	.30	.30	.30
.35	.35	.36	.35	.35	.35	.35	.30	.30	.30	.30	.30	.30	.30	.30	.30	.30	.30	.30	.30
.35	.35	.36	.35	.35	.35	.35	.30	.30	.30	.30	.30	.30	.30	.30	.30	.30	.30	.30	.30
.35	.35	.36	.35	.35	.35	.35	.30	.30	.30	.30	.30	.30	.30	.30	.30	.30	.30	.30	.30
.35	.35	.36	.35	.35	.35	.35	.30	.30	.30	.30	.30	.30	.30	.30	.30	.30	.30	.30	.30

U-VELOCITY FOR A = 4

.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
.00	.00	.00	.00	.00	.00	.00	.12	.22	.30	.34	.36	.38	.42	.51	.67	.83	.67	.99
.00	.00	.00	.00	.00	.00	.00	.41	.42	.43	.45	.46	.47	.50	.54	.54	.03	.00	.00
.00	.00	.00	.00	.00	.00	.00	.58	.61	.56	.52	.50	.49	.48	.46	.39	.00	.00	.00
.00	.00	.00	.00	.00	.00	.47	.59	.60	.57	.54	.51	.48	.44	.38	.31	.03	.00	.00
.00	.00	.00	.00	.00	.00	.47	.61	.64	.62	.58	.54	.49	.42	.33	.15	.03	.03	.00
.00	.00	.00	.00	.00	.00	.65	.73	.71	.66	.61	.56	.51	.44	.26	-.06	-.32	.34	.30
.00	.00	.00	.33	.61	.91	.98	.89	.79	.71	.64	.56	.53	.46	.38	.00	.03	.20	.00
.00	.00	.00	.39	1.03	1.29	1.15	.93	.64	.74	.66	.58	.51	.42	.33	.00	.03	.27	.00
.00	.00	.00	.97	1.51	1.48	1.23	1.00	.85	.74	.65	.55	.45	.35	.00	.03	.03	.00	.00
.00	-2.43	-.15	1.11	1.43	1.20	1.04	.91	.77	.67	.56	.44	.30	.24	.00	.00	.00	.00	.00
.00	.00	.00	.00	.00	.00	.58	.84	.60	.48	.02	.00	.00	.22	.15	.32	.00	.00	.00
.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.32	.33	.32	.00	.00	.00
.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.35	.35	.00	.00	.00
.00	.00	.00	.00	.00	.00	.00	.00	.22	.00	.00	.00	.00	.00	.34	.37	.35	.00	.00
.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00

10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27
28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45
46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63
64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81
82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99
100	101	102	103	104	105	106	107	108	109	110	111	112	113	114	115	116	117
118	119	120	121	122	123	124	125	126	127	128	129	130	131	132	133	134	135
136	137	138	139	140	141	142	143	144	145	146	147	148	149	150	151	152	153
154	155	156	157	158	159	160	161	162	163	164	165	166	167	168	169	170	171
172	173	174	175	176	177	178	179	180	181	182	183	184	185	186	187	188	189
190	191	192	193	194	195	196	197	198	199	200	201	202	203	204	205	206	207
208	209	210	211	212	213	214	215	216	217	218	219	220	221	222	223	224	225
226	227	228	229	230	231	232	233	234	235	236	237	238	239	240	241	242	243
244	245	246	247	248	249	250	251	252	253	254	255	256	257	258	259	260	261
262	263	264	265	266	267	268	269	270	271	272	273	274	275	276	277	278	279
280	281	282	283	284	285	286	287	288	289	290	291	292	293	294	295	296	297
298	299	300	301	302	303	304	305	306	307	308	309	310	311	312	313	314	315
316	317	318	319	320	321	322	323	324	325	326	327	328	329	330	331	332	333
334	335	336	337	338	339	340	341	342	343	344	345	346	347	348	349	350	351
352	353	354	355	356	357	358	359	360	361	362	363	364	365	366	367	368	369
370	371	372	373	374	375	376	377	378	379	380	381	382	383	384	385	386	387
388	389	390	391	392	393	394	395	396	397	398	399	400	401	402	403	404	405
406	407	408	409	410	411	412	413	414	415	416	417	418	419	420	421	422	423
424	425	426	427	428	429	430	431	432	433	434	435	436	437	438	439	440	441
442	443	444	445	446	447	448	449	450	451	452	453	454	455	456	457	458	459
460	461	462	463	464	465	466	467	468	469	470	471	472	473	474	475	476	477
478	479	480	481	482	483	484	485	486	487	488	489	490	491	492	493	494	495
496	497	498	499	500	501	502	503	504	505	506	507	508	509	510	511	512	513
514</																	

2

[illegible]

[illegible]

EE = 1203202-057
CE = 1203202-057
TE = 1203202-057
FE = 1203202-057

ITN = 4 [E = 1203202-057]

SAMPLE PLOTS

RUN NO: L00 7.

DISCHARGE VELOCITY : 6.84CM/SEC

DISCHARGE TEMPERATURE: 18.4°C


WIND SPEED (MAX) : 4.51M/SEC

CURRENT(JOCASEE FLOW): 4.8 CM/SEC

TOTAL SIMULATED TIME : 1.01 HRS

LENGTH SCALE(METERS) $\times 10^1$
0.00 61.00

N



ISOTHERMS AT K= 1.


LAKE KEGWEE-(RIGID-LID MODEL)

SIMULATIONS FOR FEB. 27 1979

RUN NO: LOG 7.
DISCHARGE VELOCITY : 6.84 CM/SEC
DISCHARGE TEMPERATURE: 18.4°C
WIND SPEED (MAX) : 4.51 M/SEC
CURRENT (JO CASEE FLOW): 4.8 CM/SEC
TOTAL SIMULATED TIME : 2.01 HRS

LENGTH SCALE (METERS) $\times 10^1$
0.00 61.00

N



ISOTHERMS AT K= 1.
LAKE KEOWEE-(RIGID-LID MODEL)
SIMULATIONS FOR FEB. 27 1979

RUN NO: L00 6.

DISCHARGE VELOCITY : 7.42CM/SEC

DISCHARGE TEMPERATURE: 31.7°C


WIND SPEED (MAX) : 3.09M/SEC

CURRENT(JOCSSE FLOW): 1.1 CM/SEC

TOTAL SIMULATED TIME : 1.01 HRS

LENGTH SCALE(METERS) 0.00 $\times 10^1$ 61.00

VELOCITY SCALE(CM/SEC) 0.00 12.00



VELOCITIES AT K= 1.

LAKE KEEWEE-(RIGID-LID MODEL)

SIMULATIONS FOR FEB. 27 1979

RUN NO: L00 6.

DISCHARGE VELOCITY : 7.42CM/SEC

DISCHARGE TEMPERATURE: 31.7°C


WIND SPEED (MAX) : 3.09M/SEC

CURRENT(JOCASSE FLOW): 1.1 CM/SEC

TOTAL SIMULATED TIME : 1.01 HRS

LENGTH SCALE(METERS) $\times 10^1$ 0.00 61.00

VELOCITY SCALE(CM/SEC) 0.00 12.00



VELOCITIES AT K= 2.

LAKE KEOWEE-(RIGID-LID MODEL)

SIMULATIONS FOR FEB. 27 1979

RUN NO: L00 6.

DISCHARGE VELOCITY : 7.42CM/SEC

DISCHARGE TEMPERATURE: 31.7°C

WIND SPEED (MAX) : 9.09M/SEC


CURRENT(JOCASSE FLOW): 1.1 CM/SEC

TOTAL SIMULATED TIME : 1.01 HRS

LENGTH SCALE(METERS) $\times 10^1$ 0.00 61.00

VELOCITY SCALE(CM/SEC) 0.00 12.00

N



VELOCITIES AT K= 3.

LAKE KEGONEE-(RIGID-LID MODEL)

SIMULATIONS FOR FEB. 27 1979

RUN NO: LAB 6.

DISCHARGE VELOCITY : 7.42CM/SEC

DISCHARGE TEMPERATURE: 31.7°C

WIND SPEED (MAX) : 3.09M/SEC


CURRENT(JACASSE FLOW): 1.1 CM/SEC

TOTAL SIMULATED TIME : 1.01 HRS

LENGTH SCALE(METERS) $\times 10^1$ 0.00 61.00

VELOCITY SCALE(CM/SEC) 0.00 12.00

N



VELOCITIES AT K= 4.

LAKE KEOWEE-(RIGID-LID MODEL)

SIMULATIONS FOR FEB. 27 1979

RUN NO: L00 8.

DISCHARGE VELOCITY : 7.42CM/SEC

DISCHARGE TEMPERATURE: 31.7°C

WIND SPEED (MAX) : 3.09M/SEC


CURRENT(JOYASSE FLOW): 1.1 CM/SEC

TOTAL SIMULATED TIME : 1.01 HRS

LENGTH SCALE(METERS) $\times 10^1$ 0.00 61.00

VELOCITY SCALE(CM/SEC) 0.00 12.00

N



VELOCITIES AT K= 5.

LAKE KEOWEE-(RIGID-LID MODEL)

SIMULATIONS FOR FEB. 27 1979